Multi-Point Surface Use and Operations Plan Right Hand Canyon Federal No. 1 Page 3

8. ANCILLARY FACILITIES.

None required.

9. WELLSITE LAYOUT.

- A. Exhibit G shows the dimensions of the well pad and cuttings pit, and the location of major rig components.
- B. The ground surface of the location is sloping down toward the east. Cutting will be required to level the pad area, which will be covered with at least six inches of compacted caliche.
- C. The cuttings pit will be plastic lined.
- D. A 400' x 400' work area which will contain the pad and pit area has been staked and flagged.

10. PLAN FOR RESTORATION OF THE SURFACE.

- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleared of all trash and junk, to leave the wellsite in as aesthetically pleasing a condition as possible.
- B. Unguarded pits, if any, containing fluids will be fenced until they have been filled.
- C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the Bureau of Land Management and the United States Geological Survey will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and levelled within 300 days after abandonment.

11. TOPOGRAPHY.

- A. The wellsite and access route are located in the bottom of dry wash canyon.
- B. The top soil at the wellsite is alluvium from the surrounding hills.
- C. The vegetation cover at the wellsite is moderately sparse, with prairie grasses, some yucca, and miscellaneous weeds.
- D. Cattle, goats and deer were observed during staking operations.