INSTRUCTIONS

his form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled r deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special ests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true ertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be led in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

Anhu	T. Canyon	T. Oio Alamo	T. Penn. "B"
Colt	T Stream	T. Kirtiand-Prulliand	1.10ml. C
. Salt	T 4 4-1	T Pictured Clutts	1. Feini. D
. Salt Yates864'	T. Miss	T. Cliff House	1. Leauville
	T. Devonian	T Menefee	T. Madison
Ourse	T. Cilurian	T. Point Lookout	T. Elbert
Careburg	T. Mantava	T. Mancos	T. McCracken
' San Andres	T Simpson	L Gallup	1. Ignació Otza
Glorieta	T. McKee	Base Greennom	
	T. Ellenburger		T
	T. Gr. Wash	T. Morrison	T
'. Tubb			T
Drinkard		T. Entrada	T
	T	T. Wingate	T
Wolfcamp		T. Chinle	T
_	T	T. Permain	T
'. Cisco (Bough C)		T. Penn "A"	T
		SANDS OR ZONES	
Jo 1 from	10	NT 7 6	to

(0, 1, 11011	
Jo. 2, fromto	
IMPORTA	NT WATER SANDS

nclude data on rate of water inflow and elevation to which water rose in hole.

Jo	1	from	.to	teet
10.	4,			feet
<u>ک</u>	2.	from	.10	.1661
J.	2	from	to	.feet
NO.	э.	HUIII		

LITHOLOGY RECORD (Attach additional sheet if necessary)

	_			r			
From	То	Thickness in Feet	Lithology	From	То	Thickness in Fect	Lithology
768	864	96	Anhydrite-Dolomite				
864	1,085	221	Sand - Dolomite				
	3,024	1939	Dolomite				
3024	5,528	2504	Sand – shale				
	1						
					2		