

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

clsf
up

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

RECEIVED
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

MAR 08 1993

FEB 27 1993

O. C. D.

O. C. D.

WELL API NO.

30-015-27236

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

L-6706

7. Lease Name or Unit Agreement Name

Cactus State

8. Well No.

1

9. Pool name or Wildcat

East Catclaw Draw

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Devon Energy Corporation (Nevada) ✓

3. Address of Operator

20 N. Broadway Suite 1500 OKC, OK 73102

4. Well Location

Unit Letter C : 960 Feet From The North Line and 1860 Feet From The West Line

Section 16

Township 21S

Range 26E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3295.1'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 2/17/93, we set 2,193' of 8 5/8" intermediate casing in a 12 1/4" open hole. The casing was cemented to surface with:

420 sks 35:65 (Poz:Class C) + 6% gel + 10 lb/sk Gilsonite + 1/4 lb/sk loss circulation material

150 sks Class H + 10% gypsum + 3% CaCl2 + 1/4 lb/sk loss circulation material

300 sks Class C + 2% CaCl2 (WOC = 18 hrs., PSI test = 1,000 psi)

An additional 395 sks Class C + 3% CaCl2 was pumped via 1" down the annulus. Cement was circulated to surface (9 sks).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Debby O'Donnell TITLE Engineering Technician DATE 2/19/93

TYPE OR PRINT NAME Debby O'Donnell

TELEPHONE NO. (405) 235-3611

(This space for State Use)

ORIGINAL SIGNED BY
MIKE WILLIAMS

SUPERVISOR, DISTRICT II

APPROVED BY _____ DATE _____

MAR 10 1993

CONDITIONS OF APPROVAL, IF ANY: