Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR OF DD BUREAU OF LAND MANAGEMENT DEPARTMENT DEPA

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 54298

		1411 34230
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE		6. If Indian, Allottee or Tribe Name
		7. If Unit or CA, Agreement Designation
. Type of Well Oil Gas	*	8. Well Name and No.
Oil Gas Well Other Name of Operator	7	Amaranth AMG Federal Com #1
YATES PETROLEUM CORPORATION (505) 748-1471)		9. API Well No.
3. Address and Telephone No.		30-015-27375
105 South 4th St., Artesia, NM 88210		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Wildcat Morrow
Unit B, 1310' FNL & 2630' FEL, Sec. 12-T20S-R30E - Surface		11. County or Parish, State
Unit F, 2449' FNL & 1512' FWL, Sec. 12-T20S-R30E - Proposed BHL		Eddy County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonmert Notice	Altering Casing	Conversion to Injection
	₩ Other Production Casing	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
give subsurface locations and measured and true vertice	I pertinent details, and give pertinent dates, including estimated date of starting depths for all markers and zones pertinent to this work.)*	
TI 13102'. Ran 309 joints of 5	5-1/2" casing as follows: 140 joints	of 5-1/2" 17# S-95 8rd
LT&C (5987.37'); 99 joints of !	5-1/2" 17# N-80 8rd LT&C (4190.40') ar	nd /U joints of 5-1/2"
17# N-80 Buttress LT&C (2932.73	3') (Total 13110.50') of casing set at	t 13102'. Baker float
shoe set at 13102' Baker floa	at collar set at 13055.65'. Baker DV	750 collons Surchard
Cemented in two stages as follows:	ows: Stage 1: 750 gallons mudflush,	/30 gallons surebond,
500 sacks "H", 8#/sack USE, .8.	% CF-14, .35% LWL and .35% Thriftylitenot bump plug. Went 1 barrel over dis	splacement. Shut down.
Circulated 64 eacks Circulate	ed through DV tool for 2-1/2 hours.	Stage 2: 1000 sacks
Properties Lite "H". 1/4#/sack	celloseal, 5#/sack gilsonite and .5%	CF-14 (yield 1.97,
weight 12.4). Tailed in with	100 sacks "H" with .7% CF-14 (yield 1	.18, weight 15.6). PD
8:30 PM 6-8-93. Bumped plug to	o 3500 psi for 5 minutes. Released r	ig at 10:00 AM 6-9-93.
Waiting on completion unit.	the state of the s	一大学 祝信 [[4][5]
	ACCEPTED FOR RECORD	
	CAK C sinding	The State of the S
	Jul. 1 / 1993	1000
	502. 1 1990	V A Delastra
·		
14. I hereby certify that the foregoing is true and correct	CARLSBAD, NEW MEXICO	
Signed Musty Pllen	Title Production Clerk	Date July 7, 1993
(This space for Federal or State office use)		
Approved by	Title	Date
Conditions of approval, if any:		
er en		