

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

OCT 11 1993

WELL API NO.

30-015-27463

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-3070

7. Lease Name or Unit Agreement Name

Wagon Unit

8. Well No.

1

9. Pool name or Wildcat

Undesignated Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210 (505) 748-1471

4. Well Location

Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line

Section 32 Township 22S Range 23E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4283' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole with Auger Air 8:00 AM 8-23--93. Set 40' of 20" conductor pipe. Notified NMOCD, Artesia, NM, of spud time. Resumed drilling 17 1/2" hole 12:00 AM 8-25-93. Lost returns at 90'. Drilling with no returns. Ran 8 joints 13-3/8" 54.5# J-55 casing set 360'. Guide shoe set 360', insert float set 318'. Cemented w/200 sx "H" w/12% Thixad, 10#/sx Gilsonite, 1/2#/sx Celloseal, 2% CaCl2 (yield 1.56, wt 14.6), + 250 sx PSL "C" w/10#/sx Gilsonite, 1/4#/sx Celloseal, 3% CaCl2 (yield 2.02, wt 12.4). Tailed in w/150 sx Class "C" Neat w/2% CaCl2 (yield 1.34, wt 14.8). PD 2:37 PM 8-28-93. Bumped plug to 600 psi, float held OK. Did not circulate cement. Tagged cement at 45' and redi-mix to surface with 4-1/2 yards. WOC. Drilled out 8:30 AM 8-28-93. WOC 18 hours. Cut off and weld on flow nipple. Reduced hole to 12-1/4" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TYPE OR PRINT NAME

Juanita Goodlett

TITLE

Production Supervisor

DATE 10-11-93

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

MIKE WILLIAMS

APPROVED BY

SUPERVISOR, DISTRICT II

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

OCT 29 1993