

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-015-27463

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-3070

7. Lease Name or Unit Agreement Name

Wagon AOG State

8. Well No.

1

9. Pool name or Wildcat

Wildcat Yeso

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER TITE HOLE

RECEIVED

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South Fourth Street - Artesia, NM 88210

4. Well Location

Unit Letter G : 1980 Feet From The North Line and 1980 Feet From The East Line

Section 32

Township 22S

Range 23E

NMPM

Eddy

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4283' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Perforate and acidize ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-10-94 - Nipple down wellhead and install BOP. TOOH with 2-7/8" tubign. Rig up wireline. TIH w/9-5/8" CIBP and correlated into place. Set CIBP at 2000'. Dumped 35' of cement on top of CIBP. TOOH with wireline. TIH w/2-7/8" tubing to 1271'. Spot 500 gallons 20% NEFE acid. TOOH with 2-7/8" tubing. TIH w/4" casing guns. Pressured casing to 1500 psi. Perforated 1255-1269' with 15 .42" holes (1 SPF). TOOH with casing guns and rigged down wireline. TIH w/2-7/8" tubing to 1201'. Acidized perforations 1255-1269' with 1000 gallons 20% NEFE acid and ball sealers. Swabbed. Shut well in.
6-11-94 - Swabbed. Shut well in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE Production Clerk

DATE 6-14-94

TYPE OR PRINT NAME Rusty Klein

505-748-1471
TELEPHONE NO.

(This space for State Use)

SUPERVISOR, DISTRICT II

APPROVED BY

TITLE

DATE

JUN 15 1994