

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-89143

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

NMNM88520

8. Well Name and No.

Yerba AMY Fed Com #1

9. API Well No.

30-015-27526

10. Field and Pool, or Exploratory Area

Und. Morrow

11. County or Parish, State

Eddy Co., NM

SUBMIT IN TRIPLICATE

OCT 26 1993

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL & 1580' FWL (SENW, Unit F) Section 14-T21S-R24E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☐ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other Surface, Intermediate Casing
- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☒ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded 26" hole 6:00 PM 8-29-93. Set 40" of 20" conductor. Redi-mix to surface. Notified BLM, Carlsbad, NM, of spud time. Resumed drilling 12:30 PM 9-1-93. Ran 8 joints 13-3/8" 54.5# casing set 367', Guide shoe set 367', insert float set 323'. Cemented w/200 sx Class "H" w/12% Thixad, 10# Gilsonite, 1/2# Celloseal, 2% CaCl2 (yield 1.56, wt 14.6). and 350 sx PSL "C" (65:35:6) w/10# Gilsonite, 1/2# Celloseal, 2% CaCl2 (yield 2.02, wt 12.4). Tailed in w/150 sx Class "C" Neat w/2% CaCl2 (yield 1.34, wt 14.8). PD 4:00 AM 9-2-93. Bumped plug to 200 psi, float held OK. Did not circulate. Tagged cement 40'. WOC. Drilled out 10:00 PM 9-2-93. WOC 18 hours. Reduced hole to 12 1/4" and resumed drilling. NOTE: Redi-mixed 4 1/2 yards of cement to surface. Ran 60 joints 9-5/8" 36# J-55 casing set 2690'. Guide shoe set 2690', float collar set 2648'. Cemented w/200 sx Class "H" w/12% Thixad, 10#/sx Gilsonite, 1/2#/sx Celloseal, 2% CaCl2 (yield 1.41, wt 15.2) and 1150 sx PSL w/10#/sx Gilsonite, 1/2#/sx Celloseal, 2% CaCl2 (yield 2.01, wt 12.4). Tailed in w/200 sx Class "C" w/2% CaCl2 (yield 1.32, wt 14.8). PD 2:00 PM 9-7-93. Bumped plug to 1600 psi, float held OK. Circulated 195 sacks cement. WOC. Drilled out 8:00 AM 9-8-93. WOC 18 hours. Reduced hole and resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Production Supervisor

Date 10-4-93

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title

Date

ACCEPTED FOR REC  
22 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any statement or representation to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.