

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FNL & 990' FWL of Section 10-T22S-R24E (Unit D, NWNW)

5. Lease Designation and Serial No.

NM-90505

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Atom Ant Federal Com #1

9. API Well No.

30-015-27721

10. Field and Pool, or Exploratory Area

Indian Basin Upper Penn Assoc.

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud, resume drilling,  
surface casing & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 26" hole with rat hole machine on 1-18-96. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified BLM on 1-19-96 of spudding with rat hole. Resumed drilling a 17-1/2" hole with rotary tools at 5:45 PM 1-22-96. NOTE: Notified BLM on 1-23-96 of resuming drilling.

TD 353'. Reached TD at 10:30 PM 1-23-96. Ran 8 joints of 13-3/8" 54.5# 8rd ST&C (356.63') of casing set at 353'. 1-Texas Pattern notched guide shoe set at 353'. Insert float set at 308'. Cemented with 400 sacks Premium Plus "H" and 2% CaCl2 (yield 1.32, weight 14.8). PD 2:25 AM 1-24-96. Bumped plug to 700 psi, float did not hold. Shut in. Circulated 185 sacks. WOC. Cut off and weld on flow nipple. Drilled out at 8:30 PM 1-24-96. WOC 18 hours and 5 minutes. Reduced hole to 12-1/4". Resumed drilling. NOTE: Notified Joe Lara w/BLM of running casing - did not witness.

SJS

14. I hereby certify that the foregoing is true and correct

Signed

*Rusty Kline*

Title

Production Clerk

Date

Jan. 25, 1996

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date