

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015-27739

Operator <u>Devon Energy</u>		Lease <u>Cactus State</u>		Well # <u>2</u>	
Location of Well	Unit <u>F</u>	Section <u>16</u>	Township <u>21</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>NA</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

* Witness

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	* 13 3/8	48		350	400 Surf
12 1/4	* 8 5/8	24		2200	950 Surf
7 7/8	5 1/2	15.5		4500	475 Surf

Casing Data:

Surface _____ joints of 8 5/8" inch 24 # Grade J-55

(Approved) (Rejected)

Inspected by M.S. date Feb 9-94

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required _____Type of Shoe used guide Float collar used insert Btm 3 jts welded yesTD of hole 2195' Set 2195' Feet of 8 5/8" Inch 24 # Grade J-55(New) used csg. @ 2195' with 250 270cc sacks neat cement around shoe+ 650 sax 65/25 per gal additives 10 # gilsonitePlug down @ 2:30 (AM) (PM) Date Feb 9-94Cement circulated Yes No. of Sacks 1975xCemented by Western Co. Witnessed by Mike Stubblefield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____