

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

YATES ENERGY CORPORATION

3. Address and Telephone No.

P.O. BOX 2323 ROSWELL, NM 88202 505-623-4935

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

**330' FWL + 1680' FSL
SEC 12 T-22-S. R-25-E**

5. Lease Designation and Serial No.

NM-89805

6. If Indian, Allottee or Tribe Name

7. If Unit or CA. Agreement Designation

NMNM 9102B

8. Well Name and No.

MCGRAWER HILL 12' 1200M*

9. API Well No.

30-015-27918

10. Field and Pool, or Exploratory Area

REGULATION - MORGAN

11. County or Parish, State

EDDY CO., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

Notice of Intent

Subsequent Report

Final Abandonment Notice

Approved as to plugging of the well hole.
and the well is to be abandoned until
it is determined that it is safe to plug.

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

Other

Change of Plans

New Construction

Non-Routine Fracturing

Water Shut-Off

Conversion to Injection

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

**Post ID-2
4-5-97
P&H**

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

**3/12/97 - UNSET P&H + POON W/ TBG + P&H. SET CBP @ 10,630', CAP W/ 35' CMT
IN 2 BAILEY RUNS.**

**3/13/97 - T&H W/ TBG TO 10,590'. LOAD HOLE W/ MUD. PULL TBG TO 8001'.
SPOT 60 SK CLASS 'C' CMT 8001' - 7395'. P&H W/ TBG.**

**3/14/97 - CUT OFF 5 1/2" CSG @ 3094' - COULD NOT PULL. RE-CUT CSG @ 2914'.
POON W/ TO JIS - 5 1/2" CSG. T&H W/ TBG TO 2972'. SPOT 50 SK
CLASS 'C' CMT. POON.**

**3/15/97 TAG PLUG @ 2726'. SPOT 60 SK CMT 2354'. WOC, TAG PLUG
@ 219'. RAISE TBG TO 454'. SPOT 60 SK CMT 454' - 223'.
POON W/ TBG. DIG OUT CELLAR. CUT OFF 13 3/8" + 8 5/8" CSG.
PUMP 10 SK SURFACE PLUG. WELD ON STEEL PLATE AND
DRY HOLE MARKER. CLEAN UP LOCATION. RDMO.**

14. I hereby certify that the foregoing is true and correct

Signed

Title

ENGINEER

Date

3/18/97

(This space for Federal or State office use)

Approved by **(ORIG. SGD.) ALEXIS C SWOBODA**

Title

PETROLEUM ENGINEER

Date

MAR 20 1997