orm 3160-5 June 1990)

UNI'LD STATES DEPARTMENT OF THE INTERIOR

M	01L	CONS	COMMISSION
Ţί	awer	DD	M APPROVED
T.	tesi	Budgel M	M APPROVED

CISF

Expires:	M	arch	31, 1	993
Lease Designat	ion	and	Seria	al No

BUREAU OF LAND MANAGEMENT NM-92742 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation · ~~WED SUBMIT IN TRIPLICATE Type of Well 8. Well Name and No. X Oil Well Gas Well Zingaro ANG Federal #1 2. Name of Operator 9. API Well No. YATES PETROLEUM CORPORATION (505) 748-1471)30-015-27934 3 Address and Telephone No. C OFFICE 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 Wildcat Canyon 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 2182' FNL & 872' FEL of Section 1-T22S-R23E (Unit H, SENE) 11. County or Parish, State Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent New Construction Recompletion Non-Routine Fracturing Plugging Back XX Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice X Other Resume drilling, surface Dispose Water (Note: Report results of multiple completion on Well casing & cement Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* TD 40'. Resumed drilling a 17-1/2" hole with rotary tools at 5:45 PM 8-28-94. TD 358'. Ran 8 joints of 13-3/8" 48# J-55 (362.04') of casing set at 358'. 1-Texas Pattern notched guide shoe set at 358'. Insert float set at 313.68'. Cemented with 450 sacks Class C Neat 2% CaCl2 (yield 1.32, weight 14.8). PD 12:25 AM 8-30-94. Bumped plug to 700 psi, OK. Circulated 175 sacks to pit. WOC. Drilled out at 12:30 AM 8-31-94. WOC 24 hours and 35 minutes. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Resumed drilling. 14. I hereby certify that the foregoing is true and correct Production Clerk

Title

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.