orm 3160-5 lune 1990)

UNI.) STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OIL	CONS	COMMISSIO
wer	DD	FORM APPRO

Mige 28.2 1 No. 1004-0135

	expires:	IVI a	ICII	21, 12	,,
ease	Designat	on	and	Serial	No

NM-	9	2	7	4	2

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposal RECEIVED 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE OCT 05.'94 Type of Well 8. Well Name and No. Gas Well Zingaro ANG Federal #1 2. Name of Operator 9. API Well No. (505) 748-14YATES PETROLEUM CORPORATION 30-015-27934 3 Address and Telephone No 10. Field and Pool, or Exploratory Area 105 South 4th St., Artesia, NM 88210 Wildcat Canyon 1 Tocation of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 2182' FNL & 872' FEL of Section 1-T22S-R23E (Unit H, SENE) Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Notice of Intent Abandonment New Construction Recompletion Non-Routine Fracturing Plugging Back X Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

X Other Intermediate casing &

cement

TD 2285'. Ran 51 joints of 9-5/8" 36# J-55 (2286.69') of casing set at 2285'. Float shoe set at 2285'. Float collar set at 2239.88'. Cemented with 200 sacks "H", 12% Thixad, 10#/sack gilsonite and 1/2#/sack celloseal (yield 1.56, weight 14.6) and 625 sacks Pacesetter Lite "C" (65-35-6), 5#/sack salt, 5#/sack gilsonite and 1/4#/sacks celloseal (yield 1.99,weight 12.5). Tailed in with 200 sacks Class C Neat 2% CaCl2 (yield 1.34, weight 14.8). PD 9:30 PM 9-2-94. Bumped plug to 1000#, OK. Circulated 190 sacks to pit. WOC. Drilled out at 9:45 PM 9-3-94. WOC 24 hours and 15 minutes. Nippled up and tested to 1000 psi for 15 minutes. Reduced hole to 8-3/4". Resumed drilling.

Sept. 9, 1994

→ Dispose Water

(Note: Report results of multiple completion on Well

Completion or Recompletion Report and Log form.)

that the foregoing is/true and correct 14. I hereby certify

Final Abandonment Notice

Production Clerk

(This space for Federal of State office use)

Approved by ______ Conditions of approval, if any:

Title