June 1990) DEPARTMEN'	D STATES T OF THE INTERIOR AND MANAGEMENT	NN OIL CORRECTION CISE Drawer Depires: March 31, 1993 Artesiae, Demination 2010 rial No.
Do not use this form for proposals to dri	AND REPORTS ON WELLS II or to deepen or reentry to a different reservo PERMIT—" for such proposals 12 03 m	<u> </u>
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
Type of Well Gas Well Gas Other Arrow of Operator	V	8. Well Name and No. Zingaro ANG Federal #1
YATES PETROLEUM CORPORATION 3 Address and Telephone No. 105 South 4th St., Artesia, N	(505) 748-1471)	9. API Well No. 30-015-27934 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey De 2182' FNL & 872' FEL: of Section	escription)	Wildcat Canyon 11. County or Parish, State Eddy Co., NM
	s) TO INDICATE NATURE OF NOTICE, RE	
TYPE OF SUBMISSION	TYPE OF ACT	
Notice of Intent	Abandonment Recompletion	Change of Plans
X Subsequent Report	Plugging Back Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing X Other Other Drill_cement	Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
give subsurface locations and measured and frue verti- 10-5-94 - Cleaned location, se Moved in and rigged up pulling bit, stabilizer, drill collars swivel and drilled out DV tool 6087'. Circulated clean. TOO TIH with blade bit, drill coll and began drilling cement. 10-6-94 - Continue to drill ce 10-7-94 - Continue to drill ce 10-8-94 - Continue to drill ce 10-9-94 - Continue to drill ce blade bit. TIH with bit, scra water. TOOH with tubing, scra TOOH with logging tool and rig 10-11-94 - TIH with logging to 10-12-94 - Rigged up wireline. with squeeze guns. Rigged up cement retainer and setting to	ment. ment. ment to 9805'. TOOH with 2-7/8" N per and 2-7/8" tubing to 9850'. Ci per and bit. TIH with logging tool ged down wireline. Shut down. ools and ran CBL/CCL/GR log. Rigged TIH with squeeze guns and perfora and established injection rate of 4 ools. Set cement retainer at 9150'. Broduction Clark	Made cut off on 7" casing. nstalled BOP. TIH with at 6022'. Rigged up power Drilled cement from 6024- llars, stabilizer and bit. . Rigged up power swivel 80 tubing, drill collars and rculate casing with 2% KCL and ran CBL/CCL/GR log. down wireline. Shut down. ted 4 holes at 9250'. TOOH BPM at 700 psi. TIH with
(This space for Federal for State office use)		
Approved by Conditions of approval, if any:	Title	Date Cy 1001
Title 18 U.S.C. Section 1001, makes it a crime for any perso or representations as to any matter within its jurisdiction.	on knowingly and willfully to make to any department of agency of the	United States any false, fictitious or fraudulent statements