

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED

SUBMIT IN TRIPLICATE

AUG 26 1994

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1411

3. Address and Telephone No.
105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage Sec., T., R., M., or Survey Description)
1090' FNL & 840' FWL of Section 9-T22S-R24E (Unit D, NWNW)

5. Lease Designation and Serial No.
NM-72814

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Anemone ANE Federal #2

9. API Well No.
30-015-27982

10. Field and Pool, or Exploratory Area
Wildcat Canyon

11. County or Parish, State
Eddy Co., NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
- ☒ Subsequent Report
- ☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☒ Other Intermediate casing & cement
- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 2696'. Reached TD of 12-1/4" hole at 9:15 PM 8-6-94. Ran 60 joints of 9-5/8" 36# J-55 (2698.64') of casing set at 2696'. 1-Texas Pattern notched guide shoe set at 2696'. Float collar set at 2650.82'. Cemented with 200 sacks Class H, 12% Thixad, 2% CaCl2, 10#/sack gilsonite and 1/2#/sack celloseal (yield 1.41, weight 15.2) and 1030 sacks Pacsetter Lite C, 6% gel, 10#/sack gilsonite and 1/2#/sack celloseal and 2% CaCl2 (yield 2.01, weight 12.4). Tailed in with 200 sacks Class C Neat 2% CaCl2 (yield 1.32, weight 14.8). PD 5:12 AM 8-7-94. Bumped plug to 750 psi, OK. Cement did not circulate. WOC 4 hours. Ran Temperature Survey and found top of cement at 600'. Ran 1". Tagged cement at 579'. Spotted 100 sacks Class H, 12% Thixad, 2% CaCl2, 10#/sack gilsonite and 1/2#/sack celloseal. PD 10:54 AM 8-7-94. WOC 1 hour. Ran 1". Tagged cement at 305'. Spotted 63 sacks Class C Neat. PD 12:12 PM 8-7-94. Cement circulated 13 sacks to pit. WOC. Drilled out at 5:45 AM 8-8-94. WOC 24 hours and 30 minutes. Nipped up and tested to 100# for 15 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

SJS

14. I hereby certify that the foregoing is true and correct

Signed Rusty Allen Title Production Clerk Date Aug. 10, 1994

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side