Form 3160-5 (June 1990)

14. I hereby certify that the foregoing is frue and correct

UNITED STATES DEPARTMENT OF THE INTERIOR

	- •		
M	L	CONS	COMMISSION

Drawer DD

SION	cls
RM APPROVED	

Artesia, NM 8821FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM-78214 **SUNDRY NOTICES AND REPORTS ON WELLS** 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well X Oil Well 8. Well Name and No. 2. Name of Operator Anemone ANE Federal #1 YATES PETROLEUM CORPORATION (505) 748-1471)9. API Well No. 3. Address and Telephone No. 30-015-28041 105 South 4th St., Artesia, NM 88210 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., of Survey Description) Wildcat Morrow 11. County or Parish, State 1980' FSL & 1980' FWL of Section 9-T22S-R24E (Unit K, NESW) Eddy Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction XX Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Resume drilling, surface Dispose Water (Note: Report results of multiple completion on Well casing & cement Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Resumed drilling a 17-1/2" hole with rotary tools at 8:30 AM 12-8-94. TD 350'. Reached TD at 5:00 AM 12-9-94. Ran 8 joints of 13-3/8" 48# J-55 (351.45') of casing set at 350'. 1-Texas Pattern notched guide shoe set at 350'. Insert float set at 305.15'. Cemented with 400 sacks Class C 2% CaCl2 (yield 1.33, weight 14.8). Bumped plug to 300 psi, float did not hold. Circulated 85 sacks to pit. WOC. Drilled out at 5:00 AM 12-10-94. WOC 20 hours. Cut off and weld on flow nipple. Reduced hole to 12-1/4". Resumed drilling.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, lictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CARLSBAD.NEW 🕅

Date

Production Clerk