(June 1990) DEPARTMI BUREAU OI SUNDRY NOTICE	NITED STATES ENT OF THE INTERIOR F LAND MANAGEMENT S AND REPORTS ON WELLS	Nh :L CONS COMMISSION C/S Drawer DD Artesia, NM 88249 AM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. NM-78214 6. If Indian, Allottee or Tribe Name
	drill or to deepen or reentry to a differen OR PERMIT—" for such proposals	it reservoir.
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
I. Type of Well Dil Well Gas Well Other		8. Well Name and No
2. Name of Operator YATES PETROLEUM CORPORATION	(505) 748-1471)	Anemone ANE Federal #1
3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210		30-015-28041 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., of Survey 1980' FSL & 1980' FWL of Sec	Description) tion 9-T22S-R24E (Unit K, NESW	N) Wildcat Morrow
<u></u>		Eddy Co., NM
12. CHECK APPROPRIATE BO	X(s) TO INDICATE NATURE OF NOTI	ICE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	ТҮРЕ	E OF ACTION
Notice of Intent	Abandonment Recompletion Plugging Back	Change of Plans New Construction Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Casing Casing Altering Casing Other Intermediate Cement	Water Shut-Off

TD 2670'. Reached TD at 7:15 AM 12-13-94. Ran 60 joints of 9-5/8" 36# J-55 casing set at 2670'. 1-regular guide shoe set at 2670'. Float collar set at 2625.91'. Cemented with 200 sacks "H", 12% Thixad, 10#/sack gilsonite, 1/2#/sack celloseal and 2% CaCl2 (yield 1.41, weight 15.2) and 1000 sacks Pacesetter Lite C, 10#/sack gilsonite, 1/2#/sack celloseal and 2% CaCl2 (yield 2.01, weight 12.4). Tailed in with 200 sacks Class C Neat and 2% CaCl2 (yield 1.32, weight 14.8). PD 2:52 PM 12-13-94. Bumped plug to 750 psi, OK. Cement did not circulate. WOC 5-1/4 hours. Ran Temperature Survey and found top of cement at 490'. Ran 1". Tagged cement at 490'. Spotted 50 sacks Class H, 12% thixad, 5#/sack gilsonite and 1/4#/sack celloseal. PD 9:07 PM 12-13-94. WOC 45 minutes. Ran 1". Tagged cement at 420'. Spotted 50 sacks Class H, 12% thixad, 5#/sack celloseal. PD 10:14 PM 12-13-94. WOC 45 minutes. Ran 1". Tagged cement at 230'. Spotted 35 sacks Class C Neat with 2% CaCl2. PD 11:00 PM 12-13-94. Circulated 5 sacks cement to pit. WOC. Drilled out at 4:00 PM 12-14-94. WOC 22 hours and 52 minutes. Reduced hole to 8-3/4". Resumed drilling.

<u></u>		9.
14. I hereby certify that the foregoing is the and correct Signed		Date January 4, 1995
(This space for federal or State office use)		ACCEPTED FOR RECORD
Approved by Conditions of approval, if any:	Title	
		FFR - 7 1995
Title 18 U.S.C. Section 1001, makes it a crime for any person or representations as to any matter within its jurisdiction.	knowingly and willfully to make to any department or agen	cy of the United States any false, fictitious or fraudulent statements
	*See Instruction on Reverse Side	TANESBAD, NEW MEXICO