(June 1990) DEPARTMEN'	ED STATES Γ OF THE INTERIOR AND MANAGEMENT	NM OIL CONS COMMISSION Drawer DD FORM APPROVED Artesia, Expires: March 31, 1993 5. Lease Designation and Serial No.
Do not use this form for proposals to dri	AND REPORTS ON WELLS I or to deepen or reentry to a different reser PERMIT—" for such proposals	0. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
I. Type of Well X. Oil Well Gas Well Other		8. Well Name and No.
2 Name of Operator YATES PETROLEUM CORPORATION	(505) 748-1471)	9. API Well No.
3. Address and Telephone No. 105 South 4th St., Artesia, N		30-015-28041 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., of Survey De 1980' FSL & 1980' FWL of Secti		Wildcat Morrow 11. County or Parish, State
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, R	Eddy Co., NM
TYPE OF SUBMISSION		
Notice of Intent		Change of Plans
X Subsequent Report	Recompletion Plugging Back	New Construction
Final Abandonment Notice	Casing Repair Altering Casing XX Other Production casing cement	(Note: Report results of multiple completion on Well
13. Describe Proposed or Completed Operations (Clearly state all give subsurface locations and measured and true vertice	pertinent details, and give pertinent dates, including estimated date of depths for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form) of starting any proposed work. If well is directionally drilled,
TD 10494'. Reached TD at 12:1 23 joints of 7" 26# S-95 8rd R (2454.60'); 57 joints of 7" 26 LT&C R-3 (1079.23'); 26 joints 26# N-80 8rd LT&C R-3 (2659.15 at 10460'. Float collar set a follows: Stage 1: 675 sacks (yield 1.64, weight 13.0). PD Circulated 134 sacks. Circula setter Lite C, 5#/sack salt, 5 12.5). Tailed in with 100 sac Bumped plug to 3000 psi for 5	5 AM 1-12-95. Ran 257 joints of -3 LT&C (935.29'); 60 joints of 7 # J-55 8rd LT&C R-3 (2329.59'); 2 of 7" 26# J-55 8rd LT&C R-3 (103 ') (Total 10490') of casing set a t 10420'. DV tool set at 7460'. Super C (61-15-11), .4% CF-2, .5% 10:00 PM 1-14-95. Bumped plug t ted through DV tool for 5 hours. #/sack gilsonite and 1/4#/sack ce ks "H" Neat (yield 1.18, weight 1 minutes. Released rig at 10:00 AJ pay zones. Casing bridging while	" 26# N-80 8rd LT&C R-3 6 joints of 7" 23# J-55 8rd 2.14') and 65 joints of 7" t 10460'. 1-float shoe set Cemented in two stages as CF-14 and 8#/sack Hiseal o 2800 psi for 5 minutes. Stage 2: 1400 sacks Pace- lloseal (yield 1.99, weight 5.6). PD 5:45 AM 1-15-95. M 1-15-95. NOTE: Centralized
Waiting on completion unit.		9.
14. I hereby certify that the foregoing is true and correct Signed With Hern		January 17, 1995
(This space for Federal of State office use) Approved by Conditions of approval, if any:	Title	ACCEPTED FOR RECORD
Title 18 U.S.C. Section 1001, makes it a crime for any person or representations as to any matter within its jurisdiction.	nowingly and willfully to make to any department or agency of the Soe Instruction on Reverse Side	e United States any false, fletitods or fraudulent statements CAPLSPAD, NEW MEXICC