

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

BLM Oil & Gas Division  
11-11-97

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

10-2834

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL & 660' FEL of Section 18-T22S-R24E (Unit H, SENE)

5. Lease Designation and Serial No.

NM-78215

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Hickory ALV Federal #5

9. API Well No.

30-015-28060

10. Field and Pool, or Exploratory Area

Indian Basin Upper Penn.

11. County or Parish, State Assoc.

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION


- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Production casing & cmt  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 10520'. Reached TD at 12:15 AM 11-14-97. Ran 253 joints of 5-1/2" 17# & 15.5# casing as follows: 19 joints of 5-1/2" 17# N-80 sandblasted (778.20'); 35 joints of 5-1/2" 17# N-80 varnished (1441.25'); 43 joints of 5-1/2" 17# J-55 varnished (1763.37'); 92 joints of 5-1/2" 15.5# J-55 varnished (3916.69'); 25 joints of 5-1/2" 17# J-55 varnished (1015.72') and 39 joints of 5-1/2" 17# L-80 varnished (1619.89') (Total 10535.12') of casing set at 10520'. Float shoe set at 10520'. Float collar set at 10480'. Bottom marker joint set at 9579'. Cemented with 850 sacks Super C Modified (61-15-11), .44#/sack FL25, .44#/sack FL52 and 8#/sack gilsonite (yield 1.63, weight 13.0). PD 2:15 AM 11-16-97. Bumped plug to 1700 psi for 5 minutes, OK. WOC. Released rig at 6:00 AM 11-16-97. NOTE: Displaced with 10# brine.

Waiting on completion unit.



RECEIVED

NOV 18 1997

BLM  
ROSWell, NM

14. I hereby certify that the foregoing is true and correct

Signed

*Rusty Klein*

Title Operations Technician

Date Nov. 17, 1997

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date