

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other Instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
OXY USA INC.

3. ADDRESS OF OPERATOR
P.O. BOX 50250 MIDLAND, TX 79710

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

510 FNL 1980 FEL NW-NE

OCT 19 '94

O. C. D.

14. PERMIT NO.
300152811800S01

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
ARTESIA, OFFICE
3290

5. LEASE DESIGNATION AND SERIAL NO.
NMNM9818

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
GOVERNMENT S

9. WELL NO.
6

10. FIELD AND POOL, OR WILDCAT BONE
OLD MILLMAN RANCH SPRINGS

11. SEC. T, R, M, OR BLK AND
SURVEY OR AREA

SEC 3 T20S R28E

12. COUNTY OR PARISH
EDDY

13. STATE
NM

Check Appropriate Box To Indicate Nature of Notices, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

☐
☐
☐
☐
☐

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

☐
☐
☐
☐
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

☐
☐
☐

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

☐
☐
☐

SPUD, SET CASING & CEMENT


(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and five pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRU MDC RIG #2, SPUDDED 17-1/2" HOLE @ 1830hrs CDT 9/21/94. DRILL SURFACE TO 403'. RIH W/ 13-3/8" 48# H-40 CASING & SET @ 403'. M&P 500sx CL C CMT W/ 2% CACL2 + 1/4# /sx CELLOFLAKE, DISPLACE W/ FW, PLUG DOWN @ 0945hrs CDT 9/22/94, DID NOT CIRCULATED CEMENT, WOC. RIH W/ TEMP SVY - TOC @ 200'. RIH W/ 1" & TAG @ 100', WASH DOWN TO 110'. M&P 500SX CL C CMT W/ 3% CACL2 IN 5 STAGES, DUMPING 1 TO 2' FILL OF GRAVEL BETWEEN STAGES, CIRC 25sx CMT TO PIT. CUT OFF CSG, WELD ON WH, NU BOP, DRILL AHEAD. BLM APPROVED (SHANNON SHAW) AND WITNESSED (DUNCAN WHITLOCK) CEMENTING PROCEDURE.

18. I hereby certify that the foregoing is true and correct

SIGNED



TITLE

REGULATORY ANALYST

DATE

10/18/94

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side