YATES PETROLEUM CORPORATION Walt Canyon AMA Federal #2 Section 3-T22S-R24E Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

Released RBP and pulled up. Reversed out 20 bbls. Set packer at 10014' and tested. Swabbed. Shut well in. 5-26-2000 - Swab and flow tested. Shut well in. 5-27-30-2000 - Swab & flow tested. Shut well in. 5-31-2000 - Bled tubing down. Released packer. Swabbed tubing and casing down. 6-1-2000 - Bled tubing and casing down. TOOH with tubing and packer - did not have RBP. TIH with on/off tool and latched onto RBP. TOOH with RBP. 6-2-2000 - Prep to frac. 6-3-2000 - Frac'd perforations 10096-10340' (Morrow) with 45000 gallons binary foam frac and 195809# 20-40 ac-frac black sand. Shut well in 2 hours. Opened well up and began flowing back frac. 6-4-2000 - Flowing back frac. 6-5-2000 - Flow tested. Shut well in. 6-6-2000 - Flow tested. Shut well in. 6-7-2000 - Bled well down. Pumped 300 bbls of miracle water. TIH with notched collar and tubing. Tagged up at 10196'. Circulated out sand to 10200'. Could not circulate past 10200' - sand too hard. TOOH with tubing. 6-8-2000 - TIH with bit, drill collars and tubing and tagged up at 10193'. Rigged up swivel and washed down to 10389'. Circulated out sand - hole clean. TOOH with bit, drill collars and tubing. TIH with 47 joints of tail pipe (1526'), packer, on/off tool with 1.81" profile and 150 joints of tubing. Shut down for night. 6-9-2000 - Finished TIH. Set packer at 8509' and tested. Nippled down BOP and nippled up tree. Swab & flow tested. Shut well in. 6-10-12-2000 - Flow tested. Shut well in. Released to production.

Rust Klei(ŋ

Operations Technician June 28, 2000

ACCEP	ED FOR RECC	DRD]
(ORIG.	SGD.) DAVID F	[]GL	ASS
	JL 0 6 2000		
L	QLas		
olm			