

Form 3160-9  
(June 1990)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NM OIL CONS  
Drawer DD  
Artesia, NM 88210

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well \*

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Stevens & Tull, Inc.

3. Address and Telephone No.

P. O. Box 11005, Midland, Texas 79703 915/699-1410

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1320' FWL  
Sec 6, T-21-S, R-22-E

5. Lease Designation and Serial No.  
88085

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Sweet Thing Federal Unit#

9. API Well No.

30-015-28130

10. Field and Pool, or Exploratory Area

Little Box Canyon Morrow

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Surface Casing

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/24/94 - Spud Well @ 11:00 P.M. Drlg 17 1/2" hole

10/28/94 - TD Surface hole at 402' - Lost 100% Returns @ 90'

10/29/94 - Set 13 3/8" - 54.50, K55 csg at 248'. Cement w/ 150 sx "H" + 12% Thixad + 1 10 #/sx Gilsonite + 1/4 #/sx Celloseal + 3% CaCl<sub>2</sub> + 170 sx "C" + 4% gel + 1/4 #/sx Celloseal + 2% CaCl<sub>2</sub> + 200 sx "C" + 2% CaCl<sub>2</sub>.

10/29/94 - Run Temperature Survey to 189' - Shows no cement from 189' to surface. Perf at 166' 4 spf (4 holes) and squeeze w/ 250 sx Class "C" w/ 4% CaCl<sub>2</sub> - Run Temperature Survey TOC @ 90'.

10/30/94 - Circulate cement to surface as follows:

Stage 1 - tag 90' - 30 sx "C" + 5% CaCl<sub>2</sub>

Stage 2 - Tag 90' - 30 sx "C" + 5% CaCl<sub>2</sub>

Stage 3 - Tag 90' - 30 sx "C" + 5% CaCl<sub>2</sub>

Drop 2 1/2 yds pea gravel

Stage 4 - Tag 90' - 30 sx "C" + 5% CaCl<sub>2</sub>

Stage 5 - Tag 60' - 30 sx "C" + 5% CaCl<sub>2</sub>

Stage 6 - Tag 45' - 100 sx "C" + 5% CaCl<sub>2</sub> - circulate

ACCEPTED FOR RECORD

*J. Lara*  
1 - 1994

CARLSBAD, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed

Title

Engineer

Date

11/3/94

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side