

Yates Petroleum Corporation
Anemone ANE Federal #4
API - 30-015-28133
Section 9 T22S R24E
Eddy County, NM

Perforation Record (Interval, Size, Number)

Morrow	10,296-10,308'	78 holes	.42" holes
	10,320-10,332'	78 holes	.42" holes
	10,096-10,136'	246 holes	.42" holes
	10,188-10,196'	54 holes	.42" holes
	10,206-10,214'	54 holes	.42" holes
Canyon	8010-8014'	5 holes	.42" holes
	8022-8028'	7 holes	.42" holes
	8034-8060'	27 holes	.42" holes
	7916-7942'	26 holes	.42" holes
	7946-7950'	5 holes	.42" holes
	7960-7962'	3 holes	.42" holes

Acid, Shot, Fracture, Cement Squeeze, etc.

Depth Interval	Amount and Kind of Material Used
10,296-10,332'	2000 gals 7.5% Morrow acid + 1000 SCF N2 per bbl + ball sealers
10,096-10,214'	3500 gals 7.5% Morrow acid + ball sealers
8010-8060'	3000 gals 20% gelled IC HCL + ball sealers
7916-7962'	2500 gals 20% gelled IC HCL + ball sealers
7916-7962'	40,000 gals 20% gelled IC HCL + ball sealers