State of New Mexico Form C-103 Submit 5 Copies nerals and Natural Resources Department Energy, to Appropriate Revised 1-1-89 District Office OIL CONSERVATION DIVISION DISTRICTI WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-015-28348 Santa Fe, New Mexico 87504-2088 DISTRICT II 5. Indicate Type of Lease P.O. Drawer DD. Artesia, NM 88210 FEE XX STATE DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: KEYSTONE WELL XX OTHER WELL 2. Name of Operator MARALO, INC. 3. Address of Operator Pool name or Wildcat MAR 2 4 1995 P. O. BOX 832, MIDLAND, TX 79702 BURTON FLAT, BONE SPRING ASSOCIATED 4. Well Location ALLIGO NO 80 DIV Feet From The __ : ___**660** Feet From The _ 28EDIST. 2NMPM **20S EDDY** Section Township Range County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3218' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON** CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB XX **PULL OR ALTER CASING** OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 03/03/95 LOCATION, ROAD & RESERVE PITS COMPLETE. 40' - 20" CONDUCTOR PIPE SET & CENT TO SURF. 03/05/95 SPUD WELL AT 5:45PM. 03/07/95 DRLG PLUG & CMT IN BTM OF 13-3/8" SURF. CSG. RAN 15 JTS. 13-3/8" 48# J-55 CSG. SET @ 530'. Cmtd 13-3/8" CSG W/550 SXS CL. "C" CEMT W/1/4# FLOCELE + 2% CACL .. HOLE SIZE !&-1/2", MOC 12 HRS., FILLED UP BACKSIDE 13-3/8" CSG W/3 YDS. READY MIX CENT TO SURF. NU BOF & TEST TO 1000 PSI, OK. 03/11/95 RUNNING 8-5/8" CSG. 03/12/95 RUNNING 60 JTS 8-5/8" 32# J-55 CSG SET @ 2500'. CEMT 8-5/8" CSG W/750 SXS 65/35 POZ MIX W/1/4# FLOCELE 2% CACL & TAILED IN W/200 SXS PREM CL. "C" CENT W/2% CACL. CENT CIRC'D TO SURFACE WITNESSED BY OCD. 12 HRS. MOC. SET 8-5/8" CSG SLIPS, CUT OFF 8-5/8" CSG. NU BOP, TEST TO 1000#, CK. 03/13/95 THROUGH 03/17/95 DRLG FROM 4074' to 6459'. 03/17/95 LOGGING-LOGGERS TD 6686'. SLM OUT OF HOLE FOR LOGS, MADE 30' CORRECTION 6650' - 6680'. RU SMSCO & LOGGED

CNL/LDT/GR FROM 6686' to 2400', W/GR & NEUTRON TO SURF & PHASOR INDUCTION/GR 6686' to 2500', WO LOG TRUCK. LOG TOPS:

TOP OF DELAWARE 2710' (+511') AND TOP OF BONE SPRING SAND 6326' (-3105')

整新的人 化丁克尔特代码

(SEE ATTACHED SHEET)

I hereby certify that the it	mformation above is true and o	omplete to the best of my knowled,	ge and belief.	
SIGNATURE	Jorthen	Logan	THILE REGULATORY ANALYST	DATE MARCH 21, 1995
TYPE OR PRINT NAME	DOROTHEA LOGAN	3/		TELEPHONE NO.915 684-744

(This space for State Use) ORIGINAL SIGNED BY TIM W. GUE

MAR 2 5 1995

_ DATE -

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

MARALO, INC.
KEYSTONE #5
CASING TEST & CEMENT JOB REPORT
FORM C-103

03/18/95 RD WEK RIG #1. WO COMPLETION. TEMP SURVEY TOC @ 2470' GL. FINISHED LOGGING, TIH W/ 7-7/8"
BIT, CIRC & COND HOLE, LD DP & DC'S, RU 5-1/2" CSG TOOL & RAN 155 JTS 5-1/2" 15.50# K-55 CSG.
SET @ 6680' CIRC 5-1/2" CSG., CEMT 5-1/2" CSG W/380 SXS 35/65 POZ MIX "H" CEMT W/6% D-20 +
8# PER SX D-44 + 1/4# SX D-29 + .2% D=46. TAILED IN W/250 SXS 50/50 POZ MIX "H" CEMT + .1%
D-20 + 10% D-44 + 8.5% D-112 + 2% D-46. ND & SET 5-1/2" CSG SLIPS, NU WELLHEAD, JET PITS.
RELEASED RIG @ 6:00 PM 03/18/95.