

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-28531
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Mojave AJY Com
8. Well No.	2
9. Pool name or Wildcat	Dagger Draw Upper Penn, South
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3701' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter 0 : 660 Feet From The South Line and 1980 Feet From The East Line
Section 35 Township 20 1/2 South Range 23 East NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 3:00 PM 7-1-95. Set 60' of 20" conductor pipe. Cemented to surface. NOTE: Notified OCD-Artesia of spud. Resumed drilling a 14-3/4" hole with rotary tools at 7:30 AM 7-5-95.

TD 1075'. Reached TD at 2:30 PM 7-7-95. Ran 24 joints of 9-5/8" 36# J-55 ST&C (1079.69') of casing set at 1075'. 1-Texas Pattern notched guide shoe set at 1075'. Insert float set at 1029'. Cemented with 200 sacks Class H, 12% thixad, 10#/sack gilsonite, 1/2#/sack celloseal and 2% CaCl2 (yield 1.55, weight 14.6). Tailed in with 900 sacks Pacesetter Lite, 10#/sack gilsonite, 1/4#/sack celloseal and 3% CaCl2 (yield 2.01, weight 12.3) and 200 sacks Class C 2% CaCl2 (yield 1.32, weight 14.8). PD 6:00 PM 7-7-95. Bumped plug to 800 psi, OK. Circulated 199 sacks. WOC. Drilled out at 11:00 PM 7-8-95. WOC 29 hours. Nipped up and tested to 1000# for 30 minutes, OK. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE July 12, 1995

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)
ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JUL 14 1995

CONDITIONS OF APPROVAL, IF ANY: