Submit - Copies to Appropriate District Office	State of New Mexico rgy, Minerals and Natural Resources Depart.			Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION			WELL API NO. 30-015-28729
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	P.O. Box 2088 Santa Fe, New Mexico 87504-2088			5. Indicate Type of Lease STATE STATE FEE
DISTRICT 111 1000 no Brazos Rd, Aztec, NM 87410	Santa I C, New Mickley 01201 2000			6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				7. Lease Name or Unit Agreement Name CACTUS STATE
1. Type of Well Oil Well Gas Well	⊠ other Dry & Abandoned (C) E(CEIVE(C)			
2. Name of Operator DEVON ENERGY CORPORATION (NEVADA)				- 8. Well No.
3. Address of Operator SEP 1 7 1990				9. Pool name or Wildcat
20 NORTH BROAD	WAY, SUITE 1500, OKLAHOMA CITY, C	KLAH	OMA 73102 (405) 235-3811	Catclaw Draw, East (Delaware)
4 Well Location				
Unit Letter <u>A</u> : 99	0 Feet From The <u>NORTH</u>		Line and 1190 Feet	From The <u>EAST</u> Line
Section 16 Township 21S Range 26E NMPM 10. Elevation (Show whether DF, RKB, RT, GR, etc.) GL 3233' GL 323' GL 32' GL 32				EDDY County
Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WOR	_		REMEDIAL WORK COMMENCE DRILLING OPNS.	ALTERING CASING I PLUG AND ABANDONMENT I
PULL OR ALTER CASING		_	CASING TEST AND CEMENT JOB	
OTHER:			OTHER: <u>Spud, csg strings, TD,</u>	D&AX
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.				
This well was SPUD at 1630 hrs 04-26-96 . Drld 17 1/2" hole to 390'. On 04-27-96 ran 8 jts 13 3/8" 48# H-40 8rd ST&C csg, set at 388' . Cemented 13 3/8" csg w/450 sx Class "C" + topped w/500 sx Class "C". TOC at surface. Drld 12 1/4" hole to 2100'. On 05-01-96 ran 51 jts 8 5/8" 32# K-55 8rd ST&C csg, set at 2100' . Cemented 8 5/8" csg w/200 sx BJ Srvs "C" + 655 sx 35/65 Pozmix "C" + 200 sx Class "C". Cemented 8 5/8" x 12 1/4" annulus from the top w/270 cu yds crushed 3/8" pea gravel + 150 sx "C" Neat + 1525 sx Class "C" + 2800 gals Surebond. TOC at surface. Drld 7 7/8" hole. Reached TD 3606' at 0200 hrs 05-11-96. Ran DIFL/GR/C, ZDL/CN/GR/C and SBT logs. Spotted cement plugs as follows. #1: 50 sx Class "C", tagged 2267-2214'; witnessed by Mike Stubblefield (NMOCD rep) #2: 45 sx Class "C", tagged 2070-1996'; witnessed by Mike Stubblefield #3: 20 sx Class "C", tagged 1338-1208' #4: 35 sx Class "C", tagged 462-330' #6: 16 sx Class "C", tagged 14-90' Cut off 8 5/8" SOW x 11" 3000# csg flange. Welded 1/2" steel plate on 8 5/8" csg 36" below GL. Welded on 5 1/2" dry hole marker. Well D&A at 2145 hrs 05-12-96 . Released rig at 2300 hrs.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Canti	R. Jr. ham	TITL	E ENGINEERING TECHNICIAN	DATE September 9, 1996
TYPE OR PRINT NAME	Candi Graham		. <u> </u>	TELEPHONE NO. (405) 235-3611
(This space for Stateuse) Approved by Conditions of approval, if any:	, , ,	TITL	E Tield Rep	date 11/20/96