

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert Depth	R E C T A N G U L A R C O O R D I N A T E S	Dogleg Deg/100ft	Vert Sect
7476.00	5.50	149.00	7419.09	592.42 S 366.93 E	1.90	592.42
7500.00	5.62	150.57	7442.98	594.43 S 368.10 E	0.80	594.43
7600.00	5.85	154.46	7542.48	603.29 S 372.70 E	0.45	603.29
7637.00	8.00	193.30	7579.23	607.50 S 372.92 E	13.58	607.50
7646.00	10.50	193.30	7588.11	608.91 S 372.59 E	27.78	608.91
7661.00	15.20	193.30	7602.73	612.15 S 371.82 E	31.33	612.15
7677.00	20.90	192.50	7617.94	616.99 S 370.72 E	35.66	616.99
7709.00	33.10	188.60	7646.40	631.25 S 368.17 E	38.51	631.25
7725.00	39.50	185.70	7659.29	640.65 S 367.01 E	41.40	640.65
7741.00	46.20	182.00	7671.01	651.49 S 366.30 E	44.72	651.49
7745.00	47.60	180.30	7673.75	654.41 S 366.24 E	46.77	654.41
7751.00	49.30	178.80	7677.73	658.90 S 366.28 E	33.95	658.90
7756.00	50.80	177.50	7680.94	662.73 S 366.40 E	36.02	662.73
7761.00	52.30	176.00	7684.04	666.64 S 366.62 E	38.10	666.64
7766.00	53.90	175.20	7687.05	670.63 S 366.93 E	34.46	670.63
7790.00	59.60	176.80	7700.20	690.64 S 368.32 E	24.39	690.64
7807.00	62.90	177.70	7708.38	705.53 S 369.03 E	19.96	705.53
7814.00	64.30	177.70	7711.49	711.79 S 369.28 E	20.00	711.79
7839.00	66.00	174.40	7722.00	734.42 S 370.85 E	13.77	734.42
7871.00	71.50	177.90	7733.59	764.16 S 372.84 E	19.98	764.16
7902.00	77.40	180.50	7741.90	794.01 S 373.24 E	20.67	794.01
7922.00	81.60	184.00	7745.55	813.65 S 372.47 E	27.15	813.65
7943.00	86.10	187.50	7747.80	834.41 S 370.37 E	27.09	834.41
7966.00	88.20	186.90	7748.94	857.20 S 367.49 E	9.49	857.20
7997.00	89.00	185.80	7749.70	888.00 S 364.07 E	4.39	888.00

All data is in feet unless otherwise stated.
Coordinates from slot #1 and TVD from wellhead.
Bottom hole distance is 2288.03 on azimuth 170.49 degrees from wellhead.
Vertical section is from N 0.00 W 0.00 on azimuth 180.00 degrees.
Calculation uses the minimum curvature method.
Presented by Baker Hughes INTEQ