



P.O. Box 552
Midland, Texas 79702
Telephone 915/682-1626

NIBU #27

MAY 16, 1996 - MIRU UNITED DRILL #1 AIR DRILLED 17 1/2" HOLE TO 16', SET 13 3/8" CONDUCTOR, CMTD TO SURF. WITH REDI-MIX N.U. ROTATING HEAD AND FLOWLINE. AIR/MIST DRILLED 12 1/4" HOLE TO 1210', R.U. CSG CREW, RAN 27 JTS., 9 5/8", 36#, K-55. FLOAT SHOE AT 1209, FLOAT COLLAR AT 1155', CEMENTED SURF. CSG WITH 200 SX 'C', 10% A-10, 2PPS KOLSEAL, 1/4 PPS CELLO, WT-15.1, YIELD 1.51. TAILED IN WITH 225 SX PSL 'C' WITH 6% GEL, 2% CACL2, 5PPS KOLSEAL, 1/4 PPS CELLO, WT-12.5, YIELD - 1.92. 2ND TAIL - 200 SX 'C', 2% CACL2, WT-12.5, YIELD 1.32. PLUG DOWN AT 00.15 AM, MAY 20, 1996 - CIRC'D 422 Sx TO PIT.

CUT 9 5/8", INSTALLED 11 x 9 5/8" 3M SOW CSG. HEAD. TESTED WELD TO 500 PSI.

MAY 30, 1996 - MIRU McVAY#4. N.U. BOP'S, TESTED BLIND AND PIPE RAMS, CHOKE LINES AND MANIFOLD, KILL LINES, FLOOR LINES AND SURFACE VALVES TO 300/3000 PSI. TESTED ANNULAR TO 1500 PSI.

TIH AND TAGGED CMT AT 1148' TESTED CSG TO 1750 PSI. DRILLED FLOAT COLLAR AND CEMENT TO 1205' TESTED ANNULAR TO 1750#.

DRILLED 8 3/4" HOLE TO 5325', RAN GYRO SURVEY. P.U. DIRECTIONAL BHA AND MOTOR. ROTATED AND SLIDE DRILLED TO 5915', TOH FOR HOLE IN D.P., TIH AND TAGGED UP AT 1155' AT FLOAT COLLAR. RAN IMPRESSION BLOCK, BELIEVE SURFACE CSG TO BE PARTED AT 1155'. ATTEMPTED TO RUN HOWCO 7" ALIGNMENT TOOL FAILED. SET EZ DRILL RETAINER AT 1118', SQZD 50 SX 'C' WITH 2% CACL AT 1 BPM, 200 PSI. STUNG OUT OF RETAINER, WOC, DID NOT FIND CEMENT UNDER RETAINER. FOUND 9 5/8" CSG. PARTED AT 1122, TOP OF CSG. FISH AT 1136', BTM OF FISH AT 1222', ATTEMPTED TO MILL ON FISH.

RAN 29JTS 7 5/8", 26.4# FL4-S CASING TO 1224', SHOE AT 1223', FLOAT COLLAR AT 1178'.