Form 3160-5 (June 1990)

UNITED STATES

M.		្ជាns	IVISION APPROVED
HS.	18		Budget Bureau No. 1004-0135
		. L	Expires: March 31, 1993
resia		36	S Lead Dalugnetion and Serial No.

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT NM9818 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Government 16696 OXY USA Inc. 9. API Well No. 30-015-28996 3. Address and Telephone No. P.O. Box 50250 79710-0250 10. Field and Pool, or Exploratory Area Midland, TX 915-685-5717 Winchester Morrow 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 660 FNL 660 FEL NENE (A) Sec 3 7205 Eddy NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of intent Change of Plans New Construction Non-Routine Fracturing Final Abandonment Notice Conversion to Injection 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* See other side

			.	13	
14. I hereby certify that the foregoing is true and correct Signed	Trule	David Stewart Regulatory Analyst		Date	=
(Thus space for Federal or State office use)					=
Approved by	Title			Date	_

ELM

Title 18 U.S.C. Section 1001, makes at a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictinous or fraudulent statement or representations as to any matter within its surradiction

ATTACHMENT 3160-5 OXY USA INC. GOVERNMENT S #9 SEC 3 T208 R28E EDDY COUNTY, NM

NOTIFIED BLM 7/16/97 OF SPUD. MIRU PETERSON #8, SPUD WELL @ 7/16/97. DRILL 17-1/2" HOLE TO TD @ 400', CHC. RIH W/ 13-3/8" 48# CSG & SET @ 400'. M&P 220sx 65/35 CL C/POZ W/ 6% GEL + 2% CACL2 + .25#/sx CELLOSEAL FOLLOWED BY 200sx CL C W/ 2% CaCl2, DISP W/ FW, PLUG DOWN @ 0700hrs MDT 7/17/97, CIRCULATE 41sx TO PIT, WOC 18hrs. DON EARLY W/ BLM WITNESSED CEMENT JOB. CUT OFF CASING, WELD ON STARTING HEAD, NU BOP & TEST TO 1000#, OK. RIH, TAG CMT & DRILL AHEAD.

DRILL 11" HOLE TO TD @ 3000', 7/23/97, CHC. RIH W/ 8-5/8" 24-32# CSG & SET @-3000'. M&P 1000sx 65/35 C/POZ W/ 6% GEL + 5#/sx SALT + .25#/sx CELLOFLAKE + 5#/sx GILSONITE FOLLOWED BY 200sx CL C W/ 2% CACL₂, DISP W/ FW, BUMP PLUG @ 0715hrs MDT 7/24/97. CIRCULATE 150sx TO PIT, WOC-18hrs. BLM NOTIFIED BUT DID NOT WITNESS. ND BOP, SET SLIPS & CUT CSG. NU BOP & TEST TO 5000#, HELD OK. RIH & TAG CMT, TEST CSG TO 900#, HELD OK, DRILL AHEAD.