BUREAT	UNITED STATES TMENT OF THE INTERIOR U OF LAND MANAGEMENT	WELLS	4 FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
Do not use this form for proposal Use "APPLICATIC	s to drill or to deepen or reer ON FOR PERMIT—" for such	Propose GEWEI	Ĵ
SI	JBMIT IN TRIPLICATE		If Unit or CA, Agreement Designation
1. Type of Well Dil Gas Well Well Other		JAN 22 1997	8. Weil Name and No.
2. Name of Operator			post Tank 33 Federal #4
Pogo Producing Company 3. Address and Telephone No.		DIST. 2	
P. O. Box 10340, Midland 4. Location of Well (Pootage, Sec., T., R., M., or		5)681-6822	10. Field and Pool, or Exploratory Area Undes. Delaware
-			11. County or Parish, State
660' FSL & 330' FEL, Sec	tion 33, T21S, R31E		Eddy County, NM
2. CHECK APPROPRIATE	BOX(S) TO INDICATE NA	TURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
Notice of Intent	Abando		Change of Plans
Subsequent Report			Non-Routine Fracturing
		Repair g Casing	Water Shut-Off
Final Abandonment Notice		Spud, Set Surface,	Dispose Water (Note: Report results of multiple completion on Wetl
		Inter & Prod Csg	Completion or Recompletion Report and Log form.)
<ol> <li>Describe Proposed or Completed Operations (Clear give subsurface locations and measured and</li> </ol>	rly state all pertinent details, and give pertine true vertical depths for all markers and zon	ent dates, including estimated date of starting a ses pertinent to this work.)*	my proposed work. If well is directionally drilled,
give subsurface locations and measured and ud & Set Surface Csg - MIRU Nabo s CST 12/07/96. Ran 12 jts 13-3 lliburton Lite + 2% CaCl <sub>2</sub> @ 12.7 /08/96. Recov 125 sxs excess cm tarmediate Csg - Drld 11% bole 5	rs #301. Spud @ 0800 hrs C /8" 54.5# J-55 ST&C csg. T ppg followed by 200 sxs Cl t. WOC 24 hrs. Make cut-c 35' to 3950'. TD reached @ ollar @ 3902'. Howco cmt'd n @ 0800 hrs CST 12/14/96. es w/ 250 sxs Hlliburton Li lhead & test to 1500 psi. e to 8230'. TD reached @ C 17# J-55 LT&C csg. Float 600 sxs Cl "H" + 5 pps Mic col @ 5805'. Circ 5 hrs be te + 2.8 pps KCL + .3% H322 en stages. Recov 124 sxs e " @ 14.8 ppg. Plug down.	ST 12/06/96. Drld $17-1/2$ " : PGS @ 535'. IFV @ 490'. Ho "C" + 2% CaCl <sub>2</sub> @ 14.8 ppg. off. Weld on casing head. : 0 1900 hrs CST 12/13/96. Rau 1 w/ 1050 sxs Halliburton Li Did not circ cmt. TOC @ 7 te @ 12.4 ppg. Circ 190 sx NU BOP's & test to 1500 psi 9600 hrs CST 12/23/96. Logg shoe @ 8230'. Float collar srobond + 2.4 pps KCL + .6% stween stages. Recov 110 sx 2 @ 15.6 ppg. Land plug. F excess cmt. Cmt 3rd stage w Tool closed @ 0300 hrs CST	hole to 535'. TD reached 1915 owco cmt'd csg w/ 300 sxs Plug down @ 0100 hrs CST NU BOP's & test to 500 psi. n 88 jts 8-5/8" 32# J-55 ST&C te @ 12.7 ppg followed by 200 31' by TS. Perf 8-5/8" csg @ s excess cmt to surface. ND ed well w/ Schlumberger. TIH @ 8185'. Stage tools @ 5805' H322 @ 15.6 ppg. Drop plug. s excess cmt. Cmt and stage loat held. In the bomb & open / 314 sxs Halliburg. Lite @ 12/25/96. Recov 29 sxs acess
give subsurface locations and measured and ud & Set Surface Csg - MIRU Nabo s CST 12/07/96. Ran 12 jts 13-3 lliburton Lite + 2% CaCl <sub>2</sub> @ 12.7 /08/96. Recov 125 sxs excess cm termediate Csg - Drld 11" hole 5 g. Float shoe @ 3950'. Float c is Premium Plus @ 14.8. Plug dow 1' w/ 2 holes. Cmt thru sgz hol P's & make cut-off. Weld on wel & Prod Csg - Drilled 7-7/8" hol drill pipe. Ran 190 jts 5-1/2" 3831'. Howco cmt'd 1st stage w/ oat held. Drop bomb & open DV t 514 sxs Cl "C" + 12 ppg Gilsoni tool @ 3831'. Circ 5 hrs betwe 4.4 ppg followed by 100 sxs Cl "C at. Set slips & make cut-off. N	rs #301. Spud @ 0800 hrs C /8" 54.5# J-55 ST&C csg. T ppg followed by 200 sxs Cl t. WOC 24 hrs. Make cut-c 35' to 3950'. TD reached @ ollar @ 3902'. Howco cmt'd n @ 0800 hrs CST 12/14/96. es w/ 250 sxs Hlliburton Li lhead & test to 1500 psi. e to 8230'. TD reached @ C 17# J-55 LT&C csg. Float 600 sxs Cl "H" + 5 pps Mic col @ 5805'. Circ 5 hrs be te + 2.8 pps KCL + .3% H322 en stages. Recov 124 sxs e " @ 14.8 ppg. Plug down. D BOP's & weld on wellhead	ST 12/06/96. Drld $17-1/2$ " : PGS @ 535'. IFV @ 490'. Ho "C" + 2% CaCl <sub>2</sub> @ 14.8 ppg. off. Weld on casing head. : 0 1900 hrs CST 12/13/96. Rau 1 w/ 1050 sxs Halliburton Li Did not circ cmt. TOC @ 7 te @ 12.4 ppg. Circ 190 sx NU BOP's & test to 1500 psi 9600 hrs CST 12/23/96. Logg shoe @ 8230'. Float collar srobond + 2.4 pps KCL + .6% stween stages. Recov 110 sx 2 @ 15.6 ppg. Land plug. F excess cmt. Cmt 3rd stage w Tool closed @ 0300 hrs CST	hole to 535'. TD reached 1915 owco cmt'd csg w/ 300 sxs Plug down @ 0100 hrs CST NU BOP's & test to 500 psi. n 88 jts 8-5/8" 32# J-55 ST&C te @ 12.7 ppg followed by 200 31' by TS. Perf 8-5/8" csg @ s excess cmt to surface. ND ed well w/ Schlumberger. TIH @ 8185'. Stage tools @ 5805' H322 @ 15.6 ppg. Drop plug. s excess cmt. Cmt id stage loat held. In thur Lite @ 12/25/96. Recov 29 sxs Acess
give subsurface locations and measured and ud & Set Surface Csg - MIRU Nabo s CST 12/07/96. Ran 12 jts 13-3 lliburton Lite + 2% CaCl <sub>2</sub> @ 12.7 /08/96. Recov 125 sxs excess cm termediate Csg - Drld 11" hole 5 g. Float shoe @ 3950'. Float c s Premium Plus @ 14.8. Plug dow 1' w/ 2 holes. Cmt thru sqz hol P's & make cut-off. Weld on wel & Prod Csg - Drilled 7-7/8" hol drill pipe. Ran 190 jts 5-1/2" 3831'. Howco cmt'd 1st stage w/ oat held. Drop bomb & open DV t 514 sxs Cl "C" + 12 ppg Gilsoni ' tool @ 3831'. Circ 5 hrs betwe 4 npg followed by 100 sxs Cl "C"	rs #301. Spud @ 0800 hrs C /8" 54.5# J-55 ST&C csg. T ppg followed by 200 sxs Cl t. WOC 24 hrs. Make cut-c 35' to 3950'. TD reached @ ollar @ 3902'. Howco cmt'd n @ 0800 hrs CST 12/14/96. es w/ 250 sxs Hlliburton Li lhead & test to 1500 psi. e to 8230'. TD reached @ C 17# J-55 LT&C csg. Float 600 sxs Cl "H" + 5 pps Mic ool @ 5805'. Circ 5 hrs be te + 2.8 pps KCL + .3% H322 en stages. Recov 124 sxs e " @ 14.8 ppg. Plug down. D BOP's & weld on wellhead	ST 12/06/96. Drld $17-1/2$ " : PGS @ 535'. IFV @ 490'. Ho "C" + 2% CaCl <sub>2</sub> @ 14.8 ppg. off. Weld on casing head. : 0 1900 hrs CST 12/13/96. Rau 1 w/ 1050 sxs Halliburton Li Did not circ cmt. TOC @ 7 te @ 12.4 ppg. Circ 190 sx NU BOP's & test to 1500 psi 9600 hrs CST 12/23/96. Logg shoe @ 8230'. Float collar srobond + 2.4 pps KCL + .6% stween stages. Recov 110 sx 2 @ 15.6 ppg. Land plug. F excess cmt. Cmt 3rd stage w Tool closed @ 0300 hrs CST	hole to 535'. TD reached 1915 owco cmt'd csg w/ 300 sxs Plug down @ 0100 hrs CST NU BOP's & test to 500 psi. n 88 jts 8-5/8" 32# J-55 ST&C te @ 12.7 ppg followed by 200 31' by TS. Perf 8-5/8" csg @ s excess cmt to surface. ND ed well w/ Schlumberger. TIH @ 8185'. Stage tools @ 5805' H322 @ 15.6 ppg. Drop plug. s excess cmt. Cmt id stage loat held. In the bomb & open / 314 sxs Halliburg. Lite @ 12/25/96. Recov 29 sxs acess
give subsurface locations and measured and ud & Set Surface Csg - MIRU Nabo s CST 12/07/96. Ran 12 jts 13-3 lliburton Lite + 2% CaCl <sub>2</sub> @ 12.7 /08/96. Recov 125 sxs excess cm termediate Csg - Drld 11" hole 5 g. Float shoe @ 3950'. Float c is Premium Plus @ 14.8. Plug dow 1' w/ 2 holes. Cmt thru sqz hol P's & make cut-off. Weld on wel & Prod Csg - Drilled 7-7/8" hol drill pipe. Ran 190 jts 5-1/2" 3831'. Howco cmt'd 1st stage w/ oat held. Drop bomb & open DV t 514 sxs Cl "C" + 12 ppg Gilsoni ' tool @ 3831'. Circ 5 hrs betwee 1.4 ppg followed by 100 sxs Cl "C at. Set slips & make cut-off. N 14. I hereby certify that the foregoing is true and the attract of the stage of	rs #301. Spud @ 0800 hrs C /8" 54.5# J-55 ST&C csg. T ppg followed by 200 sxs Cl t. WOC 24 hrs. Make cut-c 35' to 3950'. TD reached @ ollar @ 3902'. Howco cmt'd n @ 0800 hrs CST 12/14/96. es w/ 250 sxs Hlliburton Li lhead & test to 1500 psi. e to 8230'. TD reached @ C 17# J-55 LT&C csg. Float 600 sxs Cl "H" + 5 pps Mic ool @ 5805'. Circ 5 hrs be te + 2.8 pps KCL + .3% H322 en stages. Recov 124 sxs e " @ 14.8 ppg. Plug down. D BOP's & weld on wellhead	ST 12/06/96. Drld 17-1/2" I PGS © 535'. IFV @ 490'. H "C" + 2% CaCl <sub>2</sub> © 14.8 ppg. off. Weld on casing head. I 0 1900 hrs CST 12/13/96. Ra W / 1050 sxs Halliburton Li Did not circ cmt. TOC @ 7 Ate @ 12.4 ppg. Circ 190 sx NU BOP's & test to 1500 psi 0600 hrs CST 12/23/96. Logg shoe © 8230'. Float collar probond + 2.4 pps KCL + .6% tween stages. Recov 110 sx 2 @ 15.6 ppg. Land plug. F excess cmt. Cmt 3rd stage w Tool closed @ 0300 hrs CST & test to 2500 psi.	hole to 535'. TD reached 1915 owco cmt'd csg w/ 300 sxs Plug down @ 0100 hrs CST NU BOP's & test to 500 psi. n 88 jts 8-5/8" 32# J-55 ST&C te @ 12.7 ppg followed by 200 31' by TS. Perf 8-5/8" csg @ s excess cmt to surface. ND ed well w/ Schlumberger. TIH @ 8185'. Stage tools @ 5805' H322 @ 15.6 ppg. Drop plug. s excess cmt. Cmt id stage loat held. Brdp bomb & open / 314 sxs Hallibur Lite @ 12/25/96. Recov 29 sxs Access 12/25/96. Recov 29 sxs Access
give subsurface locations and measured and ud & Set Surface Csg - MIRU Nabo s CST 12/07/96. Ran 12 jts 13-3 lliburton Lite + 2% CaCl <sub>2</sub> @ 12.7 /08/96. Recov 125 sxs excess cm termediate Csg - Drld 11" hole 5 g. Float shoe @ 3950'. Float c is Premium Plus @ 14.8. Plug dow 1' w/ 2 holes. Cmt thru sqz hol P's & make cut-off. Weld on wel <u>&amp; Prod Csg</u> - Drilled 7-7/8" hol drill pipe. Ran 190 jts 5-1/2" 3831'. Howco cmt'd 1st stage w/ oat held. Drop bomb & open DV t 514 sxs Cl "C" + 12 ppg Gilsoni ' tool @ 3831'. Circ 5 hrs betwee 14. I hereby certify that the foregoing ty true and for Signed	<pre>rs #301. Spud @ 0800 hrs C /8" 54.5# J-55 ST&amp;C csg. T ppg followed by 200 sxs Cl t. WOC 24 hrs. Make cut-c 35' to 3950'. TD reached @ ollar @ 3902'. Howco cmt'd n @ 0800 hrs CST 12/14/96. es w/ 250 sxs Hlliburton Li lhead &amp; test to 1500 psi. e to 8230'. TD reached @ C 17# J-55 LT&amp;C csg. Float 600 sxs Cl "H" + 5 pps Mic ool @ 5805'. Circ 5 hrs be te + 2.8 pps KCL + .3% H322 en stages. Recov 124 sxs e " @ 14.8 ppg. Plug down. D BOP's &amp; weld on wellhead </pre>	ST 12/06/96. Drld 17-1/2" : PGS @ 535'. IFV @ 490'. H "C" + 2% CaCl <sub>2</sub> @ 14.8 ppg. off. Weld on casing head. : 1900 hrs CST 12/13/96. Rai W/ 1050 sxs Halliburton Li Did not circ cmt. TOC @ 7 te @ 12.4 ppg. Circ 190 sx NU BOP's & test to 1500 psi 600 hrs CST 12/23/96. Logg shoe @ 8230'. Float collar crobond + 2.4 pps KCL + .6% tween stages. Recov 110 sx 2 @ 15.6 ppg. Land plug. F excess cmt. Cmt 3rd stage w Tool closed @ 0300 hrs CST & test to 2500 psi. Operations Engineer CCEPTED FOR RECORD IG. SGD.) DAVID CM	hole to 535'. TD reached 1915 owco cmt'd csg w/ 300 sxs Plug down @ 0100 hrs CST NU BOP's & test to 500 psi. n 88 jts 8-5/8" 32# J-55 ST&C te @ 12.7 ppg followed by 200 31' by TS. Perf 8-5/8" csg @ s excess cmt to surface. ND ed well w/ Schlumberger. TIH @ 8185'. Stage tools @ 5805' H322 @ 15.6 ppg. Drop plug. s excess cmt. Cmt hd stage loat held. If bomb & open / 314 sxs Halliburg, Lite @ 12/25/96. Recov 29 sxs & cess // 1/15/97 Date
give subsurface locations and measured and ud & Set Surface Cag - MIRU Nabols s CST 12/07/96. Ran 12 jts 13-3 lliburton Lite + 2% CaCl <sub>2</sub> @ 12.7 /08/96. Recov 125 sxs excess cm termediate Cag - Drld 11" hole 5 g. Float shoe @ 3950'. Float c s Premium Plus @ 14.8. Plug dow 1' w/ 2 holes. Cmt thru sqz hol P's & make cut-off. Weld on wel & Prod Cag - Drilled 7-7/8" hol drill pipe. Ran 190 jts 5-1/2" 3831'. Howco cmt'd 1st stage w/ oat held. Drop bomb & open DV t 514 sxs Cl "C" + 12 ppg Gilsoni 'tool @ 3831'. Circ 5 hrs betwe .4 ppg followed by 100 sxs Cl "Ct. set slips & make cut-off. N 14. I hereby certify that the foregoing tyrue and for Signed	rs #301. Spud @ 0800 hrs C /8" 54.5# J-55 ST&C csg. T ppg followed by 200 sxs Cl t. WOC 24 hrs. Make cut-c 35' to 3950'. TD reached @ ollar @ 3902'. Howco cmt'd n @ 0800 hrs CST 12/14/96. es w/ 250 sxs Hlliburton Li lhead & test to 1500 psi. e to 8230'. TD reached @ C 17# J-55 LT&C csg. Float 600 sxs Cl "H" + 5 pps Mic ool @ 5805'. Circ 5 hrs be te + 2.8 pps KCL + .3% H322 en stages. Recov 124 sxs e " @ 14.8 ppg. Plug down. D BOP's & weld on wellhead nect 	ST 12/06/96. Drld 17-1/2" : PGS @ 535'. IFV @ 490'. H "C" + 2% CaCl <sub>2</sub> @ 14.8 ppg. off. Weld on casing head. : 1900 hrs CST 12/13/96. Rai W/ 1050 sxs Halliburton Li Did not circ cmt. TOC @ 7 te @ 12.4 ppg. Circ 190 sx NU BOP's & test to 1500 psi 600 hrs CST 12/23/96. Logg shoe @ 8230'. Float collar crobond + 2.4 pps KCL + .6% tween stages. Recov 110 sx 2 @ 15.6 ppg. Land plug. F excess cmt. Cmt 3rd stage w Tool closed @ 0300 hrs CST & test to 2500 psi. Operations Engineer CCEPTED FOR RECORD IG. SGD.) DAVID CM	hole to 535'. TD reached 1915 owco cmt'd csg w/ 300 sxs Plug down @ 0100 hrs CST NU BOP's & test to 500 psi. n 88 jts 8-5/8" 32# J-55 ST&C te @ 12.7 ppg followed by 200 31' by TS. Perf 8-5/8" csg @ s excess cmt to surface. ND ed well w/ Schlumberger. TIH @ 8185'. Stage tools @ 5805' H322 @ 15.6 ppg. Drop plug. s excess cmt. Cmt hd stage loat held. If bomb & open / 314 sxs Halliburg, Lite @ 12/25/96. Recov 29 sxs Scess // 55 // 1/15/97 Date

.