

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

MAY 21 1997 Oil Cons. Division

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993
BLM Artesia, NM 88210-2934
ROSWELL, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 1980' FWL of Section 6-T22S-R24E (Unit N, SESW)

5. Lease Designation and Serial No.

NM-81218

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Brannigan ANF Federal #4

9. API Well No.

30-015-29357

10. Field and Pool, or Exploratory Area

Indian Basin Upper Penn.

11. County or Parish, State Assoc.

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drilling, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 17-1/2" hole with rotary tools at 12:30 PM 5-7-97. NOTE: Notified Don Early w/BLM-Carlsbad.

TD 360'. Reached TD at 11:15 PM 5-8-97. Ran 8 joints of 13-3/8" 54.5# J-55 8rd ST&C (365.62') of casing set at 360'. 1-Texas Pattern notched guide shoe set at 360'. Insert float set at 312'. Cemented with 400 sacks Premium Plus with 2% CaCl₂ (yield 1.32, weight 14.8). PD 4:00 AM 5-9-97. Bumped plug to 600 psi, OK. Circulated 85 sacks. WOC. Nippled up and tested to 3000 psi for 30 minutes, OK. Drilled out at 11:00 PM 5-9-97. WOC 19 hours. Reduced hole to 12-1/4". Resumed drilling. NOTE: Gene Hunt w/BLM-Carlsbad witnessed.

ACCEPTED FOR RECORD

MAY 28 1997

14. I hereby certify that the foregoing is true and correct

Signed Rusty Klein Title Operations Technician Date May 19, 1997

(This space for Federal or State office use)

Approved by _____ Title _____ Date _____
Conditions of approval, if any: