

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-9194

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sacahuiste KE Federal #2

9. API Well No.

30-015-29432

10. Field and Pool, or Exploratory Area

Indian Basin Yeso South

11. County or Parish, State

Eddy Co., NM

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FWL of Section 34-T22S-R23E (Unit M, SWSW)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Production casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3400'. Reached TD at 2:00 PM 9-3-97. Ran 82 joints of 5-1/2" 15.5# casing as follows: 35 joints of 5-1/2" 15.5# J-55 sandblasted (1432.78') and 47 joints of 5-1/2" 15.5# J-55 varnished (1972.48') (Total 3405.26') of casing set at 3400'. Regular grade shoe set at 3400'. Float collar set at 3357'. Bottom marker set at 1988'. Cemented with 350 sacks Super C Modified (61-15-11), .26#/sack FL52 and 4#/sack salt (yield 1.68# weight 13.3). PD 8:45 AM 9-4-97. Bumped plug to 1500 psi for 5 minutes, OK. WOC. Released rig at 12:45 PM 9-4-97. NOTE: Displaced with 2% KCL.

Waiting on completion unit.

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date Sept. 5, 1997

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

Date