

(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BLM Oil Conservation Division
311 S. 1st Street
Albuquerque, NM 87102-2834

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 029128

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Well Name and No.

Catclaw Draw Unit #35-2

API Well No.

30-15-29723

10. Field and Pool, or Exploratory Area

Catclaw Draw (Delaware)

11. County or Parish, State

Eddy, New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other

Dry Hole

2. Name of Operator

Hallwood Petroleum, Inc.

3. Address and Telephone No.

P. O. Box 378111, Denver, CO 80237

(303) 850-6257

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

330' FNL & 1650' FEL
NW NE Section 35-T21S-R25E

12. CHECK APPROPRIATE BOX (s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Hallwood plugged and abandoned this well 11/1/97. Joe's Well Service set a retainer at 2070', pumped 25 sxs cement (neat), pulled out of retainer, pumped 25 sxs cement, est top of cement at 1610'. Tripped out of hole to 1500', circulate hole with 9# brine & salt gel (6 sxs/25 bbls). Tripped out of hole to 310', pumped 30 sxs cement, circulate 2 bbls to pit, installed dry hole market as per BLM spec.

Well is plugged as a result of an unsuccessful Delaware exploratory well in Catclaw Draw Field.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Nonya K. Durham
Production Reporting Supervisor

Date

11/12/97

(This space for Federal or State office use)

Approved by

DAVID E. CLARK

Title

PETROLEUM ENGINEER

Date

NOV 19 1997

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States, any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.