N.M C Cons. Division

cISF

-orm 3160-5 June 1990)	DEPARTME	NT OF THE INTERIOR	(i-2834 FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993	
BUREAU OF LAND MANAGEMENT			5. Lease Designation and Serial No. NM3606A	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals			6. If Indian, Allottee or Tribe Name	
	SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
1. Type of Well Oil Gas Well Well Other			8. Well Name and No.	
2. Name of Operator			Carlsbad "15" Federal Com. #1	
Mewbour	ne Oil COMPANY	10 Sec. 10	9. API Well No.	
3. Address and Telephone No.		13 CHESH	30-015-29759	
Mewbourne Oil COMPANY 3. Address and Telephone No. PO Box 5270, Hobbs, New Mexico 88241 (505)393-5905 RECARIESTA			10. Fleld and Pool, or Exploratory Area	
4. Location of Welf (Footage, Sec., T., R., M., or Survey Description)			Catclaw Draw Marrow	
	T21S - R26E L & 1850' FWL	Ŭ	11. County or Parish, State	
			Eddy County, New Mexico	
		ECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
·	TYPE OF SUBMISSION	TYPE OF ACTION		
	Notice of Intent	Abandonment	Change of Plans	
	F7	Recompletion	New Construction	
	_ Subsequent Report	Plugging Back	☐ Non-Routine Fracturing	
		Casing Repair	Water Shut-Off	
	Final Abandonment Notice	Altering Casing	Conversion to Injection	
		Other Surface & protection casing	Dispose Water	
			(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
13. Describe P directionali 01/26/98	Orilled, give subsurface locations and meas Drilled a 17 1/2" hole to 425' (lost Cemented with: 200 sx "H" plus a	ate all pertinet details, and give pertinent dates, including estimated date oured and true vertical depths for all markders and zones pertinent to this was returns at 55'). Ran 10 jnts. of 13 3/8" 48# H40 ST&C CSG add., 250 sx of lite plus add., cir. 150 sx of good cement to pay blm rep.) Waitted 18 hours on cement, tested casing to 5	ork.)* 6. to 425". oit. Plug down at	
02/02/98	Drilled a 12 1/4" hole to 2645'. Ran 65 jnts. of 32# J55 ST&C casing to 2645'. Cemented with: 200 sx of thixset 900 sx of lite and 200 sx of "C" plus 2%cc. Plug down at 12:00/AM, 02-03-98. Cir. 150 sx of good cement to pits Waited on cement for 18 hours, tested BOP's to 3000 psi, hydrill to 2000 psi (by intependent tester) tested casing to 500 psi (ok)		good cement to pits	
		ACCEPTED FOR RECORD FEB. 1.7.1988 BLM	10 (2 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	
14. I hereby ce	rtify that the foregoing is true and correct		7. 2	
Signed	View / auxune	Title Drilling Superintendent	Date 02/05/98	
(This space fo	r Federal or State office use)			

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.