			•
rm 3160-5 ine 1990)		ED STATES Γ OF THE INTERIOR	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993
	BUREAU OF L	5. Lease Designation and Serial No.	
t Do not use this for Us	6. If Indian, Allottee or Tribe Name ervoir.		
	7. If Unit or CA, Agreement Designation		
Type of Well		S P a second	8. Well Name and No.
Oil Gas Well X Well Name of Operator	L_1 Other		Spring ART Federal #1
YATES PETROLE	CORPORATION	(505) 748-1471)	9. API Well No.
3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210			<u>30-015-29825</u> 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			Wildcat Morrow
710' FSL & 1	750' FEL of Sect	lon 23-T2OS-R26E (Unit O, SWSE)	11. County or Parish, State
			Eddy Co., NM
2. CHECK A	PPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE,	REPORT, OR OTHER DATA
TYPE OF S	TYPE OF SUBMISSION TYPE OF ACTION		
Notice of	Intent	Abandonment Recompletion	Change of Plans
X Subsequer	at Report	Plugging Back	Non-Routine Fracturing
Final Aba	indonment Notice	Altering Casing X Other Spud & set cond	Conversion to Injection
3. Describe Proposed or Com	upleted Operations (Clearly state a	I pertinent details, and give pertinent dates, including estimated data details for all markers and zones pertinent to this work.)*	te of starting any proposed work. If well is directionally drilled,
give subsurface locati Spudded a 26'	ions and measured and mue vertion hole with rat h	l pertinent details, and give pertinent dates, including estimated da al depths for all markers and zones pertinent to this work.)* tole machine at 10:40 AM 8-29-97 NOTE: Notified Don Early w/BLM	. Set 40' of 20" conductor
give subsurface local Spudded a 26' pipe. Cement	ions and measured and mue vertice hole with rat h	al depths for all markers and zones pertinent to this work.)* tole machine at 10:40 AM 8-29-97 NOTE: Notified Don Early w/BLM	. Set 40' of 20" conductor
give subsurface local Spudded a 26' pipe. Cement	ions and measured and true vertice ' hole with rat h ted to surface.	al depths for all markers and zones pertinent to this work.)* tole machine at 10:40 AM 8-29-97 NOTE: Notified Don Early w/BLM	. Set 40' of 20" conductor
give subsurface local Spudded a 26' pipe. Cement	ions and measured and true vertice ' hole with rat h ted to surface.	al depths for all markers and zones pertinent to this work.)* tole machine at 10:40 AM 8-29-97 NOTE: Notified Don Early w/BLM	. Set 40' of 20" conductor -Carlsbad of spud.
give subsurface local Spudded a 26' pipe. Cement	ions and measured and true vertice ' hole with rat h ted to surface.	al depths for all markers and zones pertinent to this work.)* tole machine at 10:40 AM 8-29-97 NOTE: Notified Don Early w/BLM	. Set 40' of 20" conductor -Carlsbad of spud.
give subsurface local Spudded a 26' pipe. Cement	ions and measured and true vertian ' hole with rat h ted to surface. ting on rotary to	al depths for all markers and zones pertinent to this work.)* tole machine at 10:40 AM 8-29-97 NOTE: Notified Don Early w/BLM	. Set 40' of 20" conductor -Carlsbad of spud.
give subsurface locati Spudded a 26' pipe. Cement TD 40'. Wait TD 40'. Wait	ions and measured and true vertice ' hole with rat h ted to surface. ting on rotary to foregoing is the and correct My Willow	al depths for all markers and zones pertinent to this work.)* NOTE: Notified Don Early w/BLM pols.	. Set 40' of 20" conductor -Carlsbad of spud.

- -~

*See Instruction on Reverse Side