Form 3160-5 (November 1994)

UNITED STATES (a) DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires July 31, 1996

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side					5. Lease Serial No. LC-064490 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.		
Oil Well S Gas Well	Other		· 			Name and No.	
 Name of Operator Louis Dreyfus Natural Gas Corp. 			Language		White Wing "22" Fed Com #23 9. API Well No.		
3a. Address 14000 Quail Springs Parkway Suite 600, Oklahoma City, OK 73134 3b. Phone No. (include area code) (405) 749-75287					10. Field and Pool, or Exploratory Area Happy Valley (Morrow)		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)							
1980' FSL & 2635' FWL Sec. 22-22S-26E					11. County or Parish, State Eddy County, New Mexico		
12. CHECK AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE (OF NOTICE, R	EPORT, C	OR OTHER DATA	
TYPE OF SUBMISSION			ТҮРЕ (OF ACTION			
Notice of Intent	Acidize	☐ Deepen	Q	Production (Star	t/Resume)	☐ Water Shut-Off	
_	Alter Casing	☐ Fracture				☐ Well Integrity	
Subsequent Report	Casing Repair	New Co	onstruction 📮	Recomplete		Y Other Spud, c	asing
Final Abandonment Notice	Change Plans Convert to Injection	Plug an Plug Ba	d Abandon	Temporarily Ab Water Disposal	andon	set	
Set 20" conductor prilled 17 1/2" however well and every 5th joint (ge1) + 2% S1 (cc) 14.8 lb/gal. yield 7" 26# & 23# S-95, stage 700 sxs. Self Mixed @ 14.8 ppg, ypit thru DV tool. CelloFlake, mixed @ 14.8 px 27 Coll 25#/ 1	te to 525'. Ran shoe joint, 3, 5, ide (S-1). Circulated J-55, L&TC case thereafter. Centat 13.7 lb/gal., 1.32. Pumped 67 R 3 casing to 897 Stress cement whield 1.83 cu. ft. Cemented 2nd stage 13.2 ppg, yield	13 3/8" 5 & 7th collated 276 sing to 1 mented 10 yield 1. sxs. to 7'. DV 2#/sk. Collate w/420 st. 75 cu.	4.5# J55, llars. Ce sxs. to s 727. Cent /6/97 with 67. Tail surface. tool set @ elloFlake, ened DV too sxs. 35/65 ft./sk.	ST&C casing mented 10/urface. Description of 250 sxs Drilled 8 3959'. Can Defoam of and cir POZ-MIX casing for the control of	ng to 52/2/97 w/ Prilled sed in 00 sxs. Cl. C 3/4" ho emented er, 5#/culated ement w	25'. Centralizer (600 sxs. Cl. C 12 1/4" hole to middle of shoe Cl. C + 4% D 20 2 4 2 8 10/25/97, lst sk. Colite, 3% E 120 sx. to rese /6% gel, 25#/sk.	rs) : : : : : : :
w/2% CaC1, 25#/sk.	Celloflake mixed	@ 14.8 pp	og, yield i	l.32 cu. f	t./sk.	Closed DV tool,	
14. I hereby certify that the foregoin Name (Printed/Typed)	g is true and correct	Tated 122	Title	eserve pl	τ.		
Terrye D. Bryant	<u>, </u>			ory Techn	iciah A(CEPTED FOR RECOI	3D
Signature / Signature	was)		Date	er 11, 199	18		ijΙ
THIS SPACE FOR FEI						OCT 2 1 1999	
Approved by			Title		THE	BLM	#
Conditions of approval, if any, are a certify that the applicant holds legal which would entitle the applicant to c	or equitable title to those righ	ce does not wants in the subject	rant or Office				