Form 3160-5

vision

FORM APPROVED UNITED STATES 2834Expires: March 31, 1993 DEPARTMENT OF THE INTERIOR (June 1990) Artesia, NM 5. Lease Designation and Serial No. BUREAU OF LAND MANAGEMENT NM - 3606SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Oil Well Gas Well Lake Shore Fed. Com 10 #2 2. Name of Operator Bonneville Fuels Corporation 9. API Well No 3001529879 3. Address and Telephone No. (303) 863-1555 Suite 2200, Denver, CO 80264 10. Field and Pool, or Exploratory Area 1660 Lincoln, 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Burton Flat Morrow 11. County or Parish, State 1750' FSL, 660' FEL, Sec 10, T21S Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans ☐ Notice of Intent ACCEPTED HOR RECORD **New Construction** Recompletion Non-Routine Fracturing Plugging Back Subsequent Report Casing Repair Water Shut-Off Conversion to Injection Final Abandonmen Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/04/98 Drill to TD of 11,348'. Logged well. 3/06/98 RU & ran 11,356' L-80 LT&C casing landed at 11,344'. Cemented casing as follows: 1st stage lead of 50 sx Super H (13.ppg & yield 1.67 cf/sx) plus 70% H + 17% Pozmix A + 13% Silica flour + 2# KCL/sx+.5% Halad 344 +.4% CFR-3. Tail w/535 sx Super H(13.5 ppg & yield of 1.5 cf/sx) + 70% H + 17% Pozmix A + 13% Silica flour + 2# KCL/sx+.5% Halad 344 +.4% CFR-3.Cement 2nd stage w/lead of 550 sx Super C (13.0 ppg & yield of 1.67 cf/sx) 70% C + 17% Pozmix A + 13% Silica flour + 2# KCL/sx+.5% Halad 9. Followed w/280 sx Interfill H (11.9 ppg & yield of 2.45 cf/sx) + 50% H & Pozmix A + 10% gel +8#/sx NaCl. Tailed w/350 sx 50/50 Pozmix(14.4 ppg & yield of 1.27cf/sx).+ 50% H & Pozmix A + 2% gel +1.5#/sx KCL. Displaced cement w/ fresh water. PD @ 5:08 pm. Pressue to 3000# on casing, float held. Rig released3/8/98

14. I hereby certify that the toperoing is the and correct Signed	Operations Manager	Date6/05/98
(This space for Federal or State office use)		Date
Approved by Conditions of approval, if any:	Title	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction