			ISP
		N.M. Oil Cons.	
Form 3160-5	UNITED STATES	311 S. 1st Street	FORM APPROVED
	RTMENT OF THE INTERIOR	Artesia, NM 8821	-283 Budget Bureau No. 1004-0135
BUREA	U OF LAND MANAGEMENT		Expires: March 31, 1993 5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS			NM-0399448
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.			6. If Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT—" for such proposals			
	7. If Unit or CA, Agreement Designation		
L Type of Well			
2. Name of Operator			8. Well Name and No.
YATES PETROLEUM CORPORATION (505) 748-1471)			Malone ASA Fed Com #1
3. Address and Telephone No.			30-015-30088
105 South 4th St., Artesia, NM 88210			10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1800' FNL & 1650' FEL of Section 12-T22S-R23E (Unit G, SWSF)			Wildcat Canyon
1000 FRE & 1050 FEL OI	Section $12-T22S-R23E$ (U	nit G, SWAR	11. County or Parish, State
12. CHECK APPROPRIATE	BOX(s) TO INDICATE NATU		Eddy Co., NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			T, OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
Notice of Intent	Abandonmen	nt	Change of Plans
	Recompletion		
X Subsequent Report			
Final Abandonment Notice	Casing Repa		Water Shut-Off
		mg termediate casing &	Conversion to Injection
		ment	(Note: Report results of multiple completion on Well
13. Describe Proposed or Completed Operations (Clear	irly state all pertinent details, and give pertinent da	tes, including estimated date of starting	Completion or Recompletion Report and Log form ) any proposed work. If well is directionally drilled,
TD 2340'. Reached TD at	the vertical depuis for all markers and zones pe	runent to this work.)*	
casing set at 2340'. 1-	Texas Pattern notched gu	ide shoe set at 234	40'. Float collar set
at 2296'. Cemented with 200 sacks Class H, 10% A-10B, 10#/sack gilsonite and 1/4#/sack			
celloflake (yield 1.52, weight 14.6) and 500 sacks BJ Lite (65-35-6), 10#/sack salt, 5#/			
sack gilsonite and 1/4#/sack celloflake (yield 1.98, weight 12.8). Tailed in with 200			
sacks Class C and 2% CaCl2 (yield 1.32, weight 14.8). PD 3:00 PM 3-6-98. Bumped plug to 750 psi, OK. Cement did not circulate. WOC 4-1/2 hours. Ran Temperature Survey and			
found top of cement at 800'. Ran 1". Tagged cement at 798'. Spotted 75 sacks Class C			
and 5% CaCl2. PD 9:45 PM 3-6-98. WOC 1 hour. Ran 1". Tagged cement at 798'. Spotted			
75 sacks Class C and 5% CaCl2. PD 11:20 PM 3-6-98. WOC 1-1/2 hours. Ran 1". Tagged			
cement at 798'. Spotted 75 sacks Class C and 5% CaCl2. PD 1:20 AM 3-7-98. WOC 3 hours. Ran 1". Tagged cement at 798'. Spotted 50 sacks Class C and 5% CaCl2. PD 4:50 AM			
3-7-98. WOC $1-1/4$ hours	Ran 1". Tagged cemen	s class c and 5% ca	LIZ. PD 4:50 AM
3-7-98. WOC 1-1/4 hours. Ran 1". Tagged cement at 753'. Spotted 50 sacks Class C and 5% CaCl2. PD 7:30 AM 3-7-98. WOC 1 hour. Ran 1". Tagged cement at 750'. Spotted 100			
sacks Class C and 5% CaCl2. PD 9:00 AM 3-7-98. WOC 1 hour. Ran 1". Tagged cement at			
390'. Spotted 150 sacks Class C and 2% CaCl2. PD 10:30 AM 3-7-98. WOC 1-1/2 hours.			
Ran 1". Tagged cement at 255'. Spotted 75 sacks Class C and 1% CaCl2. PD 1:40 PM 3-7-98.			
Circulated 717 sacks. W00 out_at_2:30 AM 3-8-98.	. Nippled up and tested WOC 35 hours. Reduced h	d,to 3000 psi for 3 <u>ole to 8-</u> 374". Res	80 minutes, OK. Drilled Sumed drilling.
14. I hereby certify that the foregoing is true and co	rrect		
Signed Tusty The	Tile_Operation	ns Technician	Date March 9, 1998
(This space for Federal or Suite office use)	······		
Approved by		D FOR RECORD	Date
Conditions of approval, if any:		GD.) DAVID R GLA	
	MAR	2 0 1998	
Title 18 U.S.C. Section 1001, makes it a crime for a or representations as to any matter within its jurisdict	ny person knowingly and willfully to make to any tion	department or agency of the United	States any false, fictitious or fraudulent statements

\*See Instruction on Reverse Side

