

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. 311 S st
Artesia, NM

10-2034

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1800' FNL & 1650' FEL of Section 12-T22S-R23E (Unit G, SWNE)

5. Lease Designation and Serial No.

NM-0399448

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Malone ASA Fed Com #1

9. API Well No.

30-015-30088

10. Field and Pool, or Exploratory Area

Wildcat Canyon

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Acidize perforations

☐ Change of Plans

☐ New Construction

☐ Non Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-21-98 - Moved in and rigged up pulling unit.

5-22-98 - Bled well down. Pumped 50 bbls 2% KCL down tubing and annulus. TOOH with subpump. TIH with packer, RBP and tubing. Set RBP at 7700' and tested to 1000 psi. Set packer at 7500'. Loaded annulus and tested to 1000#.

5-23-26-98 - Acidized perforations 7562-7664' (Canyon) with 20000 gallons gelled 20% iron control HCL acid and ball sealers. Released packer and RBP. TOOH. Rigged up spoolers. RIH with subpump. Released well to production department.

ACCEPTED FOR RECORD

JUL 01 1998

BLM

14. I hereby certify that the foregoing is true and correct

Signed

Rusty Klein

Title Operations Technician

Date May 28, 1998

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date

RECEIVED
MAY 29 8:26
CONTACT OF LAND RIGHT
ROSWELL OFFICE