

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004 0135  
Expires: March 31, 1991  
5. Lease Designation and Serial No.

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals

**SUBMIT IN TRIPLICATE**

NM-045276  
6. If Indian, Allottee or Tribe Name  
7. If Unit or CA, Agreement Designation  
8. Well Name and No.  
Preston Federal #25  
9. API Well No.  
30-015-30120  
10. Field and Pool, or Exploratory Area  
Wildcat Morrow  
11. County or Parish, State  
Eddy Co., NM

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other  
2. Name of Operator  
YATES PETROLEUM CORPORATION (505) 748-1471  
3. Address and Telephone No.  
105 South 4th St., Artesia, NM 88210  
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
660' FSL & 2310' FWL of Section 34-T20½S-R23E (Unit N, SESW)

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud, conductor, resume  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut Off  
☐ Conversion to Injection  
☐ Dispose Water

13. Describe Proposed or Completed Operations if clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.\*

Spudded a 26" hole with rat hole machine at 4:00 PM 6-4-98. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Gene Hunt w/BLM-Carlsbad of spud. Resumed drilling a 14-3/4" hole with rotary tools at 7:45 PM 6-8-98.

TD 1105'. Reached TD at 10:00 AM 6-9-98. Ran 25 joints of 9-5/8" 36# J-55 8rd ST&C (1107.96') of casing set at 1105'. 1-Texas Pattern notched guide shoe set at 1105'. Insert float set at 1015'. Cemented with 200 sacks "H", 10% A-10B, 1/4#/sack celloflake, 10#/sack gilsonite and 1% CaCl2 (yield 1.52, weight 14.56) and 600 sacks "C" (65-35-6), 5#/sack gilsonite, 1/4#/sack celloflake and 2% CaCl2 (yield 1.90, weight 12.6). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.34, weight 14.8). PD 4:30 PM 6-9-98. Bumped plug to 910 psi, OK. Circulated 275 sacks. WOC. Nipped up and tested to 3000 psi for 30 minutes, OK. Drilled out at 6:00 PM 6-10-98. WOC 25 hours and 30 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Witnessed by Don Early w/BLM-Carlsbad.

ACCEPTED FOR RECORD  
(ORIG. SGD) DAVID R. GLASS  
JUN 15 1998

14. I hereby certify that the foregoing is true and correct

Signed

*Rusty Allen*

Title Operations Technician

Date June 11, 1998

Approved by

Conditions of approval, if any:

Title

Date