

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

**SUBMIT IN TRIPLICATE**

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-045276

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Preston Federal #25

9. API Well No.

30-015-30120

10. Field and Pool, or Exploratory Area

Wildcat Morrow

11. County or Parish, State

Eddy Co., NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 2310' FWL of Section 34-T20S-R23E (Unit N, SESW)

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other 4-1/2" liner & cement  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 9520'. Reached TD of 6-1/8" hole at 11:00 PM 11-13-98. Ran 35 joints of 4-1/2" 11.6# N-80 (1474.60') of liner set at 9520'. Float shoe set at 9520'. Float collar (landing collar) at 9476'. Cemented with 160 sacks Super C Modified (61-15-11), 6/10% FL25, 6/10% FL52 and 5#/sack gilsonite (yield 1.64, weight 13.0). PD 12:22 AM 11-19-98. Bumped plug to 2100 psi for 1 minute, OK. WOC. Released rig at 2:00 PM 11-19-98. NOTE: Displaced with 10# brine water.

Waiting on completion unit.

ACCEPTED FOR RECORD

DEC 3 1998

(ORIG. SGD) GARY GOURLEY

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date Nov. 20, 1998

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date