			N.M. Oll Lan	is. Divisio	<u>C</u>	
Form 3160-5 June 1990)	UNITED STAT DEPARTMENT OF THI BUREAU OF LAND MA	E INTERIOR	11 S. 1st Stra Artesia, NM	01 210-Base Bu Expires	M APPROVED ireau No. 1004-0135 5: March 31, 1993 ation and Serial No.	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals				6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE				7. If Unit or CA	A, Agreement Designation	
1. Type of Well Oil Well X Well Other Other					d No.	
2. Name of Operator				Little Box Canyon AOX Fed #2		
YATES PETROLEUM CORPORATION (505) 748-1471) 3. Address and Telephone No.				30-015-30222		
105 South 4th St., Artesia, NM 88210				10. Field and Pool, or Exploratory Area		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				Little Box Canyon Morrow		
1980' FNL & 1190' FWL of Section 7-T21S-R22E (Unit E, SWNW)				11. County or Pa	rish, State	
				Ede	dy Co., NM	
12. CHECK APP	ROPRIATE BOX(s) TO INE	DICATE NATURE	OF NOTICE, REPOI			
TYPE OF SUBMISSION TYPE OF ACTION						
Notice of Inter		Abandonment		Change of	Plans	
[V]		Recompletion				
X Subsequent Re	port	Plugging Back		Non-Routine Fracturing		
Final Abandonment Notice Casing Repair Water Shut-Off Conversion to Injection Conversion to Injection						
			surface casing		•	
		cemen	t		ults of multiple completion on Well completion Report and Log form)	
	d Operations (Clearly state all pertinent deta and measured and true vertical depths for a			g any proposed work	If well is directionally drilled,	
26". Set 40'	44" hole with rat hole of 20" conductor pipe id. Resumed drilling	. Cemented to	surface. NOTE:	Notified	l Gene Hunt w/BLM -	
casing set at 306'. Cemente and 1% CaCl2 (sack celloflak (yield 1.34, w circulate. WO PD 9:20 PM 7-2 and 4% CaCl2. 25 sacks Class 119'. Spotted Tagged cement 10 sacks to pi	te office use)	n notched guide s C, 10% A-10B, .6) and 275 sac 12.8). Tailed PM 7-26-98. H Tagged cement a an 1". Tagged WOC 1 hour. 11:40 PM 7-26-9 .4% CaCl2. PD acks Class C an welded on flow ed hole to 12-4	shoe set at 35 10#/sack gilso ks Poz C (65-35 in with 200 sa sumped plug to 4 at 142'. Spotte cement at 140'. Ran 1". Tagged 8. WOC 1 hour. 12:45 AM 7-27-9 ad 4% CaCl2. PD	3'. Inser onite, 1/4 5-6), 5#/sa acks Class 25 psi, 0k d 50 sacks Spotted cement at Ran 1". 98. WOC 45 1:50 AM 5 GRDout at irriling.	et float set at //sack celloflake ack gilsonite, 1/4#/ C and 2% CaCl2 C. Cement did not s Class C 4% CaCl2. 25 sacks Class C t 137'. Spotted Tagged cement at 5 minutes. Ran 1". 7-27-98. Circulated	
		ORIG. SGD.) GA	RY GOURLEY			
Title 18 U.S.C. Section 1001, multor representations as to any matter	ces it a crime for any person knowingly and within its jurisdiction.			l States any false, fie	citious or fraudulent statements	
