

73413

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

Operator <u>Newbourne Oil Co</u>		Lease <u>N.E. AVALON "36" State</u>		Well # <u>1</u>	
Location of Well	Unit	Section	Township	Range	County
Drilling Contractor	<u>Peterson</u>		Type of Equipment		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement

Casing Data:

Surface 70 joints of 9 5/8 inch 36 # Grade J-55

(Approved) (Rejected)

Inspected by Van Barten date 12-7-98

Cementing Program

Size of hole 12 1/4 Size of Casing 9 5/8 Sacks cement requiredType of Shoe used _____ Float collar used ☒ Btm 3 1/2 jts welded strapTD of hole 2708 Set 2708 Feet of 9 5/8 Inch 36 # Grade J-55(New) used csg. @ 2708 with _____ sacks neat cement around shoe
+ _____ sack additives 3005X Thick Set H 550 SX Brite 250 SX
"C" #12010 cncd Plug down 10'30 12-8-98Plug down @ 10:30 (AM) (PM) Date 12-8-98Cement circulated No No. of Sacks _____Cemented by B.T. Witnessed by _____Temp. Survey ran @ 4:00 (AM) (PM) Date 12-8-98 top cement @ 1350

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: 1" AG Per Attached