

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

| | |
|-----------------------------------|------------------------------------------------------------------------|
| WELL API NO. | 30-015-30390 |
| Indicate Type of Lease | STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| State Oil & Gas Lease No. | |
| Lease Name or Unit Agreement Name | Northeast Avalon Hills "36" State |
| Well No. | 1 |
| Pool name or Wildcat | Burton Flats; Morrow (73280) |

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | |
| Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER | |
| Name of Operator Mewbourne Oil Company | |
| Address of Operator PO Box 5270, Hobbs, New Mexico 88240 (505)393-5905 | |
| Well Location Unit Letter O : 660 Feet From The South Line and 1980 Feet From The East Line 36 Section 20S Township 27E Range NMPM Eddy County | |
| Elevation (Show whether DF, RKB, RT, GR, etc.) 3235 GR | |

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/02/98 Spudded a 17 1/2" hole and drilled to 434'. Ran 13 3/8" 48# H40 ST&C casing to 434'. Cemented with 200 sks of Thickset "H" + 10% A-10B + 1/4# / SK Celloflake + 10 #/ sk Gilsonite, 220 sks of BJ Lite + 6% Gel + 1/4# / sk Celloflake + 2% CaCl2, 200 sks of Class "C" + 2% CaCl2. Plug down at 2:15 pm, 12-02-98. Did not circulate. Top of Cement at 37'. Fill hole with 3 yards of readymix. Waited on cement for 18 hours. Tested casing to 500 psi before drilling out.

Drilled out with a 12 1/4" bit to 2708'. Ran 9 5/8" 36# J55 ST&C and set at 2708'. Cemented with 300 sks of Thickset "H" 10% A-10B + 10 #/ sk Gilsonite + 1/4# / sk Celloflake + 0.5 CaCl2, 550 sks of BJ Lite + 6% Gel + 5#/sk Salt + 5#/sk Gilsonite + 1/4# / sk Celloflake. Tailed with 250 sks of Class "C" + 2% CaCl2. Did not circulate. PLug down at 10:30 am 12-08-98. Waited 6 hrs and ran a Temp. Survey, top of cement at 1100'. Set 16 cement plugs via 1" tubing, using 1125 sks of Class "C" + 7% CaCl2. Circulate 10 sks to pits. 12-10-98 Tested Casing to 1500 psi before drilling out.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Matthews TITLE Drilling Superintendent DATE 12-11-98

TYPE OR PRINT NAME Steve Matthews TELEPHONE NO. 393-5905

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY B67 TITLE DATE 12-23-98

CONDITIONS OF APPROVAL, IF ANY