


YATES PETROLEUM CORPORATION
Archimedes ARE State Com #2
Section 18-T21S-R24E
Eddy County, New Mexico

SUNDRY NOTICE CONTINUED:

and 8092-8104' (2 SPF - Strawn). TOOH with casing guns. Rigged down wireline and lubricator. TIH with RBP, packer and tubing to 7981'.
12-7-99 - Finished TIH with tools. Set RBP at 8716'. Pulled up and set packer at 8587'. Acidized perforations 8664-8670' with 500 gallons 7-1/2% Morrow HCL acid. Moved tools and straddled perforations 8412-8421'. Acidized with 500 gallons 7-1/2% Morrow HCL acid. Moved tools and straddled perforations 8236-8242'. Acidized with 1000 gallons 7-1/2% Morrow HCL acid. Moved tools and set RBP at 8716'. Set packer at 8174'. Straddled perforations 8236-8670' and swabbed. Shut well in.
12-8-99 - Swab and flow tested. Shut well in.
12-9-99 - Flowed well down. Loaded tubing with 2% KCL. Released packer and RBP. Pulled up and set RBP at 8141' and tested. Set packer at 8012'. Acidized perforations 8092-8104' (Strawn) with 1000 gallons 15% iron control HCL acid. Swabbed. Shut well in.
12-10-99 - Swab and flow tested. Shut well in.
12-11-13-99 - Bled well down. Pumped 40 bbls 2% KCL water. Released packer and RBP. TOOH with tubing, packer and RBP. TIH with packer with 1.875" profile nipple and tubing. Set packer at 8012'. Nippled down BOP and nipped up tree. Tested packer to 500 psi. Swabbed well in. Shut well in.


Rusty Klein
Operations Technician
December 30, 1999