

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd, Aztec, NM
87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-30581

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
CARLSBAD "22H" FEE COM.

(originally named Carlsbad "22H"
State Com. #2)

8. Well No.

2

Pool name or Wildcat

AVALON (MORROW)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other D&A

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address of Operator

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Well Location

Unit Letter H : 1350 Feet From The NORTH Line and 660 Feet From The EAST Line

Section 22 Township 21S Range 26E NMPM EDDY County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

GL 3143'

Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: spud through D&A ☒

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

This well spud on 04-02-1999 at 0415 hrs and drld 17 1/2" hole to 429'. On 04-03-1999 ran 9 jts 13 3/8" 48# H-40 ST&C csg, set at 428'; cemented w/670 sx Class "C". Tagged cement w/1" pipe outside 13 3/8" csg. Topped w/200 sx Class "C"; TOC at surface. WOC 19 hrs.

Drld 12 1/4" hole to 2200'. On 04-08-1999 ran 50 jts 8 5/8" 32# K-55 LT&C csg, set at 2199'; cemented w/735 sx 35/65/6 Pozmix "C" + 200 sx Class "C"; ran Temp Svy. Topped w/200 sx Class "H" + 1000 sx Class "C". On 04-14-1999 Computalog ran CBL.

Drilled 7 7/8" hole. Reached TD 11,200' at 1700 hrs 05-03-1999 On 05-04-1999 Schlumberger ran Azimuthal Laterolog Micro-CFL/NGT and 3 Detector Litho-Density Compensated Neutron/NGT logs.

Pumped drilling mud TD to 10,483'. Set 7 cement plugs from 10,483' to surface; total 135 sx Class "H" + 170 sx Class "C"; drilling mud between each plug. Cut off 8 5/8" csg and welded on 1/2" steel plate. Carlsbad "22H" Fee Com. #2 was D&A 05-08-1999.

Released rig at 1200 hrs 05-08-1999..

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Candace R. Graham

TITLE ENGINEERING TECHNICIAN

DATE June 4, 1999

TYPE OR PRINT NAME Candace R. Graham

TELEPHONE NO. (405) 235-3611

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM

DISTRICT II SUPERVISOR

Approved by AW TITLE _____

Conditions of approval, if any:

DATE 6-9-99