

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-015-30635
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-4100
7. Lease Name or Unit Agreement Name	Jacque AQJ State
8. Well No.	3
9. Pool name or Wildcat	Lost Tank Delaware, West

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	

4. Well Location Unit Letter <u>N</u> : <u>330</u> Feet From The <u>South</u> Line and <u>1650</u> Feet From The <u>West</u> Line Section <u>34</u> Township <u>21S</u> Range <u>31E</u> NMPM Eddy County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3465' GR
---	--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3960'. Reached TD at 7:45 AM 5-21-99. Ran 89 joints of 8-5/8" 32# J-55 8rd ST&C (3965.33') of casing set at 3960'. 1-regular guide shoe set at 3960'. Float collar set at 3912'. Cemented with 800 sacks Halliburton Interfill C, 1/4#/sack flocele (yield 2.48, weight 11.9). Tailed in with 250 sacks Premium Plus with 2% CaCl2 (yield 1.34, weight 14.8). PD 7:15 PM 5-21-99. Bumped plug to 1603 psi, OK. Circulated 175 sacks. WOC. Nipped up and tested to 3000 psi for 30 minutes. Drilled out at 9:15 PM 5-22-99. WOC 26 hours. Reduced hole to 7-7/8". Resumed drilling. NOTE: Cement job witnessed by E. L. Martinez with OCD-Artesia.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 4, 1999  
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 6-9-99  
CONDITIONS OF APPROVAL, IF ANY: