

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-30635

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-4100

7. Lease Name or Unit Agreement Name
Jacque AQJ State

8. Well No.
3

9. Pool name or Wildcat
Lost Tank Delaware, West

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter N : 330 Feet From The South Line and 1650 Feet From The West Line
Section 34 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3465' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Production casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8129'. Reached TD at 4:15 AM 5-28-99. Ran 189 joints of 5-1/2" 17# & 15.5# casing as follows: 18 joints of 5-1/2" 17# J-55 8rd sandblasted (795.70'); 12 joints of 5-1/2" 17# J-55 8rd varnished (539.37'); 18 joints of 5-1/2" 15.5# J-55 8rd varnished (771.11'); 40 joints of 5-1/2" 15.5# J-55 8rd varnished (1711.72'); 5 joints of 5-1/2" 15.5# J-55 8rd sandblasted (194.09'); 91 joints of 5-1/2" 15.5# J-55 8rd varnished (3903.00'); 5 joints of 5-1/2" 17# J-55 8rd varnished (225.86') (Total 8140.85') of casing set at 8129'. Float shoe set at 8129'. Float collar set at 8082'. DV tool set at 6023'. Bottom marker set at 7288'. Top marker set at 4117'. Pumped 500 gallons of mud flush and 500 gallons of Super Flush 102 ahead of cement. Cemented in two stages as follows: Stage 1: 450 sacks Super H, .4% CFR3, 5#/sack gilsonite, .5% Halad 344 and 1#/sack salt (yield 1.66, weight 13.0). PD 12:45 AM 5-30-99. Bumped plug to 1100 psi for 5 minutes. Circulated 68 sacks. Circulated thru DV tool for 4 hours. Stage 2: 275 sacks Interfill C, .25#/sack flocele and 5#/sack gilsonite (yield 2.78, weight 11.5). Tailed in with 600 sacks Super H, .4% CFR3, 5#/sack gilsonite, .5% Halad 344 and 1#/sack salt (yield 1.66, weight 13.).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 4, 1999

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-14

(This space for State Use)

APPROVED BY Jim W. Green TITLE District Supervisor DATE 6-9-99

CONDITIONS OF APPROVAL, IF ANY: