X | Subsequent Report

Final Abandonment Notice

Well Integrity

Csg set depth

X Other Corn 9 5/8"

O	U1ED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEME NORY NOTICES AND REPORTS to not use this form for proposals to drill or to andoned well. Use Form 3160-3 (APD) for s	ON WARTESIA, NM 88210-2 On wartesia, NM 88210-2	Expires: November 30, 2000	
	IN TRIPLICATE - Other instructions	on reverse side	7. If Unit or CA/Agreement, Name and/or No	
1. Type of Well Oil Well X Gas Well 2. Name of Operator V Santa Fe Snyder Corpo	8. Well Name and No. Roaring Springs "14" Fed Com #7 9. API Well No. 30-015-30845 10. Field and Pool, or Exploratory Area Dagger Draw South (Upper Penn) 11. County or Parish, State			
3a. Address 3b. Phone No. (include area code) 550 W. Texas, Suite 1330, Midland, TX 79701 915-686-6612				
4. Location of Well (Footage, Sec., 1980' FSL & 2310' FEL				
12. (OUTCOL ADDRODDIATE DOV/EO. TO		Eddy NM	
12,	CHECK APPROPRIATE BOX(ES) TO	INDICATE NATURE OF NOTICE, REPO	PRT, OR OTHER DATA	
TYPE OF SUBMISS	TYPE OF SUBMISSION TYPE OF ACTION			
Notice of Intent	Acidize	Deepen Produ	ction (Start/Resume) Water Shut-Off	

Describe Proposed or Coommpleted Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once tosting has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.) 13.

Fracture Treat

New Construction

Plug and Abandon

Plug Back

Reclamation

Recomplete

Water Disposal

Temporarily Abandon

This sundry is to correct the setting depth of the 9 5/8" csg as reported on 12-30-99.

Convert to Injection

Alter Casing

The previous depth reported was 1215' the correct setting depth for the 9 5/8" csg is 1208'. The cement was reported correctly on the report dated 12-30-99

> ACCEPTED FOR RECORD (ORIG. SGD.) GARY GOURLEY

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)	Title				
Bill Keathly	Regulatory Specialist				
Gier Zearlly	Date 1-6-00				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by	Title	Date			
Conditions of approval, if any, are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject lea which would entitle the applicant to conduct operations thereon.	or Office	<u> </u>			

CECEIVED