

A Gyrodata Directional Survey

MEASURED DEPTH feet	IN CL deg.	AZIMUTH deg.	BORE HOLE BEARING deg. min.	DOGLEG SEVERITY deg./ 100 ft.	VERTICAL DEPTH feet	CLOSURE DIST. AZIMUTH feet deg.	HORIZONTAL COORDINATES feet
2300.0	4.27	142.74	S 37 16 E	1.30	2299.5	16.7 225.4	11.70 S
2400.0	4.79	135.54	S 44 28 E	0.77	2399.2	18.9 200.8	17.65 S
2500.0	5.99	128.88	S 51 7 E	1.35	2498.7	23.9 179.3	23.90 S
2600.0	7.52	119.89	S 60 6 E	1.85	2598.1	32.0 161.8	30.44 S
2700.0	8.84	114.44	S 65 33 E	1.53	2697.0	43.3 148.4	36.88 S
2800.0	10.42	117.84	S 62 10 E	1.68	2795.6	58.1 139.6	44.28 S
2900.0	12.19	116.37	S 63 38 E	1.80	2893.7	76.6 134.0	53.19 S
3000.0	12.67	114.21	S 65 47 E	0.67	2991.3	97.3 129.9	62.38 S
3100.0	14.22	114.10	S 65 54 E	1.55	3088.6	119.8 126.9	71.90 S
3200.0	14.30	112.78	S 67 13 E	0.33	3185.5	143.9 124.6	81.70 S
3300.0	13.52	109.84	S 70 10 E	1.05	3282.6	167.4 122.7	90.45 S
3400.0	13.87	111.89	S 68 7 E	0.60	3379.7	190.6 121.3	98.89 S
3500.0	14.38	117.87	S 62 8 E	1.55	3476.7	214.8 120.5	109.16 S
3600.0	13.69	115.57	S 64 26 E	0.89	3573.7	239.0 120.2	120.07 S
3700.0	13.45	114.08	S 65 55 E	0.42	3670.9	262.4 119.7	129.92 S
3800.0	13.69	116.66	S 63 20 E	0.65	3768.2	285.8 119.3	139.98 S
3900.0	12.24	118.54	S 61 28 E	1.50	3865.6	308.2 119.2	150.35 S
4000.0	12.48	120.17	S 59 50 E	0.42	3963.3	329.6 119.2	160.84 S
4100.0	13.04	119.15	S 60 51 E	0.61	4060.8	351.7 119.2	171.77 S
4200.0	12.43	115.14	S 64 52 E	1.08	4158.4	373.7 119.1	181.84 S
4300.0	14.06	117.85	S 62 9 E	1.74	4255.7	396.6 119.0	192.08 S
4400.0	14.16	119.78	S 60 13 E	0.48	4352.7	421.0 119.0	203.83 S
4500.0	13.36	118.73	S 61 16 E	0.84	4449.8	444.7 119.0	215.46 S
4600.0	13.11	120.19	S 59 49 E	0.42	4547.2	467.6 119.0	226.71 S
4700.0	10.96	119.46	S 60 32 E	2.15	4645.0	488.5 119.0	237.09 S
4800.0	11.18	118.48	S 61 31 E	0.29	4743.1	507.7 119.0	246.38 S
4900.0	12.05	117.20	S 62 48 E	0.91	4841.0	527.8 119.0	255.78 S