

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	Course Length FT	True Vertical Depth	Vertical Section FT	N-S FT	E-W FT	CLOSURE		Dogleg Severity Deg/100	BUILD RATE Deg/100
								Distance FT	Direction Deg		
6977.00	8.90	106.90	93.00	6871.07	956.43	-425.50	856.80	956.64	116.41	1.18	-1.18
7073.00	10.00	113.20	96.00	6965.76	972.11	-430.95	871.57	972.29	116.31	1.57	1.15
7146.00	10.00	115.20	73.00	7037.66	984.79	-436.14	883.13	984.96	116.28	.48	.00
7242.00	8.50	112.00	96.00	7132.41	1000.21	-442.35	897.25	1000.36	116.24	1.65	-1.56
7336.00	7.50	115.20	94.00	7225.49	1013.28	-447.56	909.24	1013.43	116.21	1.16	-1.06
7430.00	7.00	115.20	94.00	7318.74	1025.14	-452.61	919.98	1025.29	116.20	.53	-.53
7558.00	8.00	113.80	128.00	7445.64	1041.84	-459.53	935.18	1041.99	116.17	.79	.78
7653.00	9.00	114.50	95.00	7539.60	1055.88	-465.28	947.99	1056.02	116.14	1.06	1.05
7747.00	9.60	114.40	94.00	7632.36	1071.07	-471.57	961.82	1071.20	116.12	.64	.64
7843.00	10.20	115.20	96.00	7726.93	1087.58	-478.49	976.80	1087.70	116.10	.64	.62
7906.00	11.00	113.30	63.00	7788.86	1099.16	-483.25	987.37	1099.29	116.08	1.39	1.27
7977.00	11.70	112.00	71.00	7858.47	1113.12	-488.62	1000.27	1113.23	116.04	1.05	.99
8129.00	11.60	110.50	152.00	8007.34	1143.74	-499.75	1028.87	1143.82	115.91	.21	-.07
8225.00	11.80	110.40	96.00	8101.34	1163.14	-506.55	1047.11	1163.20	115.82	.21	.21
8310.00	11.00	108.90	85.00	8184.66	1179.86	-512.20	1062.93	1179.90	115.73	1.00	-.94
TD Projection to Bit											
8350.00	11.00	108.90	40.00	8223.93	1187.44	-514.68	1070.15	1187.48	115.68	.00	.00